UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT	5. LEASÉ DESIGNATION AND SERIAL NO.
	SF 077092B
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.	OF THE ON TRIBE NAME
Use "APPLICATION FOR PERMIT-" for such proposals	
SUBMIT IN TRIPLICATE	7. IF UNIT OR CA, AGREEMENT DESIGNATION
1. TYPE OF WELL	HOUCK
	8. WELL NAME AND NO.
OIL WELL GAS WELL OTHER :	#2C
2. NAME OF OPERATOR	9. API WELL NO.
CONOCO INC. 3. ADDRESS AND TELEPHONE NO.	30-045-30142
	10. FIELD AND POOL, OR EXPLORATORY AREA
P.O. Box 2197, DU 3066, Houston, TX 77252-2197 (281) 293-1613	BLANCO MESA VERDE
the state of the s	11. COUNTY OR PARISH, STATE
660' FNL 750' FWL, SECTION 11, T29N, R10W, UNIT LETTER?	SAN JUAN COUNTY
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, F	REPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE O	DF ACTION
Notice of Intent Abandonment	
	Change of Plans
Subsequent Report Recompletion	New Construction
Final Abandonment Notice	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Altering Casing	Conversion to Injection
Other: Casing Report	Dispose Water
	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)
directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent. 5/25/00 Well spudded on 5/25/00 at 5:00 p.m. 5/26/00 Drilled surface hole. Ran 7 joints, 9-5/8", 36#, J-55, ST&C casing set at 274'. Cement v. 20 BWOC CaC12 Calcium Chlor + .25 LB/SK Cello-Flake. Displaced with 19 bbl fresh held. Bumped plug at 7:00 a.m. 5/26/00 with 240psi. 5/28/00 Ran 47 joints, 7", 20#, J-55, ST&C casing set at 1,824'. Stage 1: Cement with 232 sxs of BWOC CaC12, Calcium Chlor + .25 LBS/SK Cello-Flake + 8.0% BWOC Bentonite. Stage 1: Cement with 232 sxs of BWOC CaC12, Calcium Chlor + .25 LBS/SK Cello-Flake + 8.0% BWOC Bentonite.	with 150 sxs of Neat Cement Type III + water. Circulate to surface. Floats of Neat Cement Premium Lte + 2.0%
Neat Cement + 2.0% BWOC CaC12, Calcium Chlor + .25 LBS/SK Cello-Flake. Float He Bumped plug at 5:00 p.m. on 5/28/00 with 1,000 psi. Ran 120 joints, 4-1/2", 10.5#, J-55, ST&C casing set at 5,105'. Cement with 250 sxs of BWOC Bentonite + .25 BWOC Cello-Flake + .65 BWOC FL-62 + 35.0% BASE Poz + .20	Class H Blend 35:65 Poz:H + 6.0 0 BWOC CD-32 + 10.0 BWOC CSE
Float held. Displace with 80 bbls fresh water. Bumped plug at 7:00 a.m. on 6/1/00 with	n 1,550 psi.
14. I hereby certify that the foregoing is true and correct SIGNED TITLE DEBRA SITTNER, As Agent	t for Conoco Inc.ACOUTETATEOR RECOI
(This space for Federal or State office use)	
	DATE AUG 3 2000
APPROVED BY TITLE Conditions of approval, if any:	DATE

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.