UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

		ces and Repo	CO OII W			
			* .		5.	Lease Number
Time of Woll					6.	SF-076465 If Indian, All. on
Type of Well GAS					. , 0.	Tribe Name
GAS				•		TITUE Name
Name of Operator				56780	7.	Unit Agreement Na
BURLING	TON		(3) L			
RESOURC	-1	GAS COMPANY		18 2001		
			C 200		3 415%	Well Name & Number
Address & Phone			(3 3)	active of the	35	Cornell B #100
PO Box 4289, Fa	rmington, NM	87499 (505)	326-97	8. CON. 3	<i>₹</i> 9.	API Well No.
			- \{\cdot\cdot\cdot\cdot\cdot\cdot\cdot\cdot	Olo.	7	30-045-30198
Location of Well			TAT NINATONA	1/35	10.	Field and Pool Fulcher Kutz PC
1075'FNL, 1315'F	ыь, sec.14, 1	-29-N, K-12-	M' MATERIA	Sec 22 15 Mgs 2	11.	
				مستطالك والتصا	4.4	San Juan Co, NM
						·
CHECK APPROPRIA					OTHER	DATA
Type of Submissi			Type of		of p1	ane
X Notice o	I Intent	Abandon Recompl		_X_ Change	nstruc	
Subseque	nt Report	Pluggin				Fracturing
bubseque	ne Report	Casing			Shut o	-
Final Ab	andonment	X Alterin				o Injection
		Other -		- 		_
	osed or Compl ed to alter t		ons	& cement pro	gram o	f the subject
It is intend well. Revisions: Mud Program: Interval	ed to alter t	he approved	ons	& cement pro		f the subject
It is intend well. Revisions: Mud Program:	ed to alter t Type Spud	he approved Weight	ons casing	Fluid Loss		f the subject
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program	ed to alter t Type Spud Non-dispers	Weight 8.4-9.0 sed 8.4-9.0	ons casing Vis. 40-50 30-60	Fluid Loss No control No control		
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size	Type Spud Non-dispers	Weight 8.4-9.0 sed 8.4-9.0	ons casing Vis. 40-50 30-60	<u>Fluid Loss</u> No control		<u>e</u>
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program	ed to alter t Type Spud Non-dispers	Weight 8.4-9.0 sed 8.4-9.0 rval Casing	ons casing Vis. 40-50 30-60	Fluid Loss No control No control Weight	<u>Grad</u>	<u>e</u>
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram:	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7"	ons casing Vis. 40-50 30-60 Size	Fluid Loss No control No control Weight 20.0# 10.5#	<u>Grad</u> J-55 K-55	<u>e</u>
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Prog. 7" surface cas.	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement	ons casing Vis. 40-50 30-60 Size 1/2" w/3% ca	Fluid Loss No control No control Weight 20.0# 10.5#	<u>Grad</u> J-55 K-55	<u>e</u>
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program 7" surface cas: (54 cu.ft. of	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks	vis. 40-50 30-60 Size 1/2" w/3% caculate t	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface).	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program 7" surface cas: (54 cu.ft. of	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program: (54 cu.ft. of 4 1/2" product flocele, 5 program for the following flocele, 5 program for the flocele, 5 product flocele, 5 program for the flocele, 5 product flocele, 5 p	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program 7" surface cas: (54 cu.ft. of	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program: (54 cu.ft. of 4 1/2" product flocele, 5 program for the following flocele, 5 program for the flocele, 5 product flocele, 5 program for the flocele, 5 product flocele, 5 p	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program: (54 cu.ft. of 4 1/2" product flocele, 5 program for the following flocele, 5 program for the flocele, 5 product flocele, 5 program for the flocele, 5 product flocele, 5 p	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
It is intend well. Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program 7" surface cas: (54 cu.ft. of	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program (54 cu.ft. of 4 1/2" product flocele, 5 pt 1/4#/sack flo	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge occle (399 cu.	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with ft., 100% exce	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit s Type III cm	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program (54 cu.ft. of 4 1/2" product flocele, 5 pp 1/4#/sack flo	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge occle (399 cu.	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with ft., 100% exce	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit s Type III cm	Grad J-55 K-55 e, 0.25 h 2% ca	<u>e</u> pps flocele lcium chloride, 0.25 1% calcium chloride,
Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program (54 cu.ft. of 4 1/2" product flocele, 5 pp 1/4#/sack flo	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge occle (399 cu.	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with ft., 100% exce	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack ss to ci	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit s Type III cm rculate to su	Grad J-55 K-55 e, 0.25 h 2% ca	e pps flocele lcium chloride, 0.25 1% calcium chloride,
Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program (54 cu.ft. of 4 1/2" product flocele, 5 pp 1/4#/sack flo	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ge occle (399 cu.	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with ft., 100% exce	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack ss to ci	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit s Type III cm	Grad J-55 K-55 e, 0.25 h 2% ca	e pps flocele lcium chloride, 0.25 1% calcium chloride,
Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program (54 cu.ft. of 4 1/2" product flocele, 5 pp 1/4#/sack flo	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ga occele (399 cu.:	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with ft., 100% exce Title	vis. 40-50 30-60 Size 1/2" w/3% caculate the Premium 90 sack ss to ci	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit s Type III cm rculate to su	Grad J-55 K-55 e, 0.25 h 2% caut with inface).	e pps flocele lcium chloride, 0.25 1% calcium chloride, te 2/28/01 TLW
Revisions: Mud Program: Interval 0-120' 120-1944' Casing Program Hole Size 8 3/4" 6 1/4" Cementing Program (54 cu.ft. of 4 1/2" product flocele, 5 pp 1/4#/sack flo	Type Spud Non-dispers Depth Inter 0-120' 0-1944' ram: ing - 46 sx Cla f slurry, 200% ion liner - lea ps LCM-1, 8% ga occele (399 cu.:	Weight 8.4-9.0 sed 8.4-9.0 rval Casing 7" 4 ass "B" cement excess to cir ad w/120 sacks el. Tail with ft., 100% exce Title	vis. 40-50 30-60 Size 1/2" w/3% caculate t Premium 90 sack ss to ci	Fluid Loss No control No control Weight 20.0# 10.5# lcium chlorid o surface). Lite cmt wit s Type III cm rculate to su	Grad J-55 K-55 e, 0.25 h 2% caut with inface).	e pps flocele lcium chloride, 0.25 1% calcium chloride,