Form 3160-5 (June, 1990)

Signed:

Conditions of approval, if any:

res or representations as to any matter within its jurisdiction.

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVE
--------------

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

Date: January 23, 2002

SUNDRY NOTICES AND REPORTS ON WELLS SF-079968 Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir. 6. If Indian, Allotte or Tribe Name Use "APPLICATION FOR PERMIT--" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Other Gas Well Ropco 4-2 2. Name of Operator Q. API Well No. Richardson Operating Company 30-045-30422 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 1700 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000 Twin Mounds PC 4. Location of Well (Footage, T, R, M, or Survey Description) 11. County or Parish, State 1552' FSL, 784' FEL San Juan County, NM Sec. 4-T29N-R14W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment New Construction Notice of Intent Recompletion Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Subsequent Report Conversion to Injection Altering Casing Surface Casing/Cementing Dispose Water Final Abandonment Notice port results of multiple completion on Well Other: see below 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)\* Spud 83/4" surface hole. Drift to 140'. 5/31/01 Drill to 140°. Ran 3 jts 7" 20# casing and set at 132°. Cemented with 40 sxs of Class "B" with 2% KCL. 5/31/01 Circulated 4 bbls to surface.WOC 12 Hours TD well at 1100'. Run 25 jts 4 1/2" 10.5# casing and 4 jts 4 1/2" 10.5# casing to 1096.35'KB. Precede cement with 06/1/01 10 bbls water. Cemented with 12 sxs of C-Lite with 2% sodium mescalite, 1/4# Cello. Tail with 100 sxs Class "B" Neat, 1/4# Cello. Release plug. Displace with 16.5 bbls water. Secure Location

· The Military on Reverse Sale

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, flictitious or fraudulent

Title: Operations Manager

Mit