Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

FORM APPROVED
Budget Bureau No. 1004-0135
Expires November 30, 2000

5 1	Page	Seria	l No

6	If Indian	Allottee or Tribe Name	2

abandoned well. Use For				SF081078	4
SUBMIT IN TRIPLICATE	- Other instruction	ns on reverse side			/Agreement, Name and/or N
1. Type of Well Oil Well Well Gas Other		DFC 200	H 3	8. Well Name ar CHAVEZ GAS	
2. Name of Operator XTO Energy Inc.		Property of		9. API Well No.	
3a. Address		3b. PhoneNo. (include area c		30-045-3071	.1
2700 Farmington Ave., Bldg. K. Ste		NM 87401505-324-109	00		ol, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1235 'FSL & 740 'FWL SWSW, UL M, Sec 23, T29N, R10W				BASIN DAKOT. MESAVERDE	A/BLANCO
1235'FSL & 740'FWL SWSW, UL M, S		TOM		11. County or Pa	arish. State
29				SAN JUAN	NM
12. CHECK APPROPR	IATE BOX(ES) TO I	NDICATE NATUREOF NO	TICE, REPOR	r,orotherdat	ΓΑ
TYPE OF SUBMISSION		TYP	E OF ACTION		
Notice of Intent	Acidize	Deepen	Production	on (Start/Resume)	Water Shut-Off
_	Alter Casing	Fracture Treat	Reclama	ion	Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recompl	ete	X Other TD well. Set
Final Abandonment Notice	Change Plans	Plug and Abandon	Tempora	rily Abandon	& cmt prod csg.
	Convert to Inject	ction Plug Back	Water Di	sposal	

Describe Proposed or CoommpletedOperation (clearly state all pertinent details, including estimated starting date of any proposed work and approximated uration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final AbandonmentNotices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

Ran 155 joints 4-1/2", 10.5#, J-55, STC csg.to 6,841' KB. Cemented Reached TD of 6,850' on 11/4/01. 4-1/2" production casing @ 6,841' w/175 sx Premium Lite HS cement (65/35/6 Type III/poz/gel) w/1/4 pps celloflake, 0.20% dispersant, 0.50% FL, 2% KCl & 6 pps gilsonite (mixed @ 11.9 ppg, 2.39 cuft/sx) lead slurry followed by 200 sx Premium Lite HS cement (65/35/6 Type III/poz/gel) w/1/4 pps celloflake, 0.20% dispersant, 0.50% FL, 2% KCl & 6 pps gilsonite (mixed @ 12.5 ppg, 2.00 cuft/sx) tail slurry. Released Bearcat Drlg Rig #1 on 11/6/01. Ran temp survey. Found TOC @ 700'.

14. I hereby certify that the foregoing is true and correct Name(Printed/Typed)	Title OPERATIONS ENGINEE	D	
RAY MARTIN (Kay Martin	Date 12/11/01	Acidana	
THIS SPACE FOR FEDERA	AL OR STATE OFFICE USE	The state of the s	
Approved by	Title	Date 7 7 7001	
Conditions of approval, if any, are attached. Approval of this notice does not warran certify that the applicant holds legal or equitable title to those rights in the subject lewhich would entitle the applicant to conduct operations thereon.	nt or Office ease	FAIRING SAME	