UNITED STATES DEPARTMENT OF THE INTERIOR

Sundry Notices and Reports on Wells	
	. Lease Number NMSF078197 . If Indian, All. or
Type of Well GAS	Tribe Name
Name of Operator BURLINGTON FEB 2002	. Unit Agreement Name
Address & Phone No. of Operator	. Well Name & Number Nye Federal #1M . API Well No.
PO Box 4289, Farmington, Nil 87499 (303) 320 3700	30-045-30798
1830'FNL, 1020'FWL, Sec.8, T-29-N, R-10-W, NMPM	 Field and Pool Otero Chac/Blanco I Basin Dakota
1	1. County and State San Juan Co, NM
. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTH	IER DATA
Type of Submission Type of Action	
Notice of Intent Abandonment Change of	Plans
	ne Fracturing
Casing Repair Water Shut	coff
Z Subsequent Report — Flugging Back — Water Shut — Casing Repair — Water Shut — Altering Casing — Conversion — X Other - Spud, casing, & cement	t off n to Injection
Casing Repair Water Shut Final Abandonment Altering Casing Conversion	t off n to Injection
Casing Repair Water Shut Final Abandonment Altering Casing Conversion X Other - Spud, casing, & cement	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Tinal Abandonment Casing Repair Altering Casing Conversion X Other - Spud, casing, & cement Total Abandonment 1/24/02 MIRU. 1/25/02 Spud well @ 12:00 am 1/25/02. Drill to 171'. Circ TIH w/8 jts 8-5/8" 32.3# WC-50 ST&C csg, set @ 3 Class "B" neat w/3% calcium chloride, 0.25 pps f Circ 19 bbls cmt to surface. WOC. NU BOP. PT BOP 30 mins, OK. Drilling ahead.	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Casing Repair Water Shute Altering Casing Conversion X Other - Spud, casing, & cement	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Casing Repair Water Shute Altering Casing Conversion X Other - Spud, casing, & cement	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Casing Repair Water Shut Altering Casing Conversion X Other - Spud, casing, & cement	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Casing Repair Water Shut Altering Casing Conversion X Other - Spud, casing, & cement	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Tinal Abandonment Casing Repair Altering Casing Conversion X Other - Spud, casing, & cement Total Abandonment 1/24/02 MIRU. 1/25/02 Spud well @ 12:00 am 1/25/02. Drill to 171'. Circ TIH w/8 jts 8-5/8" 32.3# WC-50 ST&C csg, set @ 3 Class "B" neat w/3% calcium chloride, 0.25 pps f Circ 19 bbls cmt to surface. WOC. NU BOP. PT BOP 30 mins, OK. Drilling ahead.	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Tinal Abandonment ———————————————————————————————————	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Tinal Abandonment ———————————————————————————————————	n to Injection thole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.).
Tinal Abandonment Casing Repair Altering Casing Conversion Conversion Conversion Conversion Conversion Altering Casing Conversion Conversion Conversion Total Abandonment 1/24/02 MIRU. 1/25/02 Spud well @ 12:00 am 1/25/02. Drill to 171'. Circ TIH w/8 jts 8-5/8" 32.3# WC-50 ST&C csg, set @ 3 Class "B" neat w/3% calcium chloride, 0.25 pps f Circ 19 bbls cmt to surface. WOC. NU BOP. PT BOP 30 mins, OK. Drilling ahead. APD ROW Related	hole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.). & csg to 600 psi/
Tinal Abandonment ———————————————————————————————————	hole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.). & csg to 600 psi/
Final Abandonment Casing Repair Altering Casing Conversion Other - Spud, casing, & cement Other - Spud, casing, & cement 1/24/02 MIRU. 1/25/02 Spud well @ 12:00 am 1/25/02. Drill to 171'. Circ TIH w/8 jts 8-5/8" 32.3# WC-50 ST&C csg, set @ 3 Class "B" neat w/3% calcium chloride, 0.25 pps f Circ 19 bbls cmt to surface. WOC. NU BOP. PT BOP 30 mins, OK. Drilling ahead. APD ROW Related 4. I hereby certify that the foregoing is true and correct.	nole clean. TOOH. 53'. Cmtd w/250 sxs locele (295 cu. Ft.). & csg to 600 psi/

MUS