

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTSUBMIT IN DUPLICATE*
(See other instructions on reverse side)FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NMSF078197

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Nye Federal #1M

9. API WELL NO.

30-045-30798

10. FIELD AND POOL, OR WILDCAT

Otero Chacra/Blanco MV/Basin DK

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec.8, T-29-N, R-10-W

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:

OIL WELL ☐GAS WELL ☒DRY ☐Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒WORK OVER ☐DEEP-EN ☐PLUG BACK ☐DIFF. RESVR ☐Other ☐

DHC-2978

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL & GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1830'FNL, 1020'FWL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH
San Juan13. STATE
New Mexico15. DATE SPUDDED
1/25/200216. DATE T.D. REACHED
2/4/200217. DATE COMPL. (Ready to prod.)
5/2/200218. ELEVATIONS (DF, RKB, RT, BR, ETC.)*
5747' GL, 5759' KB

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD
6906'21. PLUG, BACK T.D., MD & TVD
6742'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

3142-3412' Chacra

25. WAS DIRECTIONAL SURVEY MADE
No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Array Induction, Compensated Neutron-Litho Density, GR/CCl

27. WAS WELL CORED
No

CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8	32.3#	353'	12 1/4	295 cu. Ft.	
4 1/2	10.5#	6903'	7 7/8	2620 cu. Ft.	

LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8	6562'	

TUBING RECORD

PERFORATION RECORD (Interval, size and number)	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
3142, 3144, 3152, 3214, 3216, 3218, 3220, 3222, 3235, 3240, 3244, 3248, 3255, 3261, 3266, 3269, 3280, 3295, 3308, 3316, 3322, 3326, 3330, 3336, 3338, 3351, 3384, 3387, 3402, 3406, 3412	
	DEPTH INTERVAL (MD)
	3142-3412'
	AMOUNT AND KIND OF MATERIAL USED
	651 bbls 20# lnr gel, 200,000# 20/40 Brady sand, 113 Mscf N2.

33. DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)
	Flowing	SI

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO
4/24/2002	3 hrs						
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)	
SI 625	SI 625			311 Separator			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)	TEST WITNESSED BY
To be sold	

35. LIST OF ATTACHMENTS
None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE Regulatory Supervisor

DATE 5/6/2002

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; core intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCR.	CONTENTS, ETC.	GEOLOGIC MARKERS		
					NAME	MEAS. DEPTH	TRUE VERT. DEP
Ojo Alamo	880'	996'	White, cr-gr ss.		Ojo Alamo	880'	
Kirtland	996'	1555'	Gry sh interbedded w/tight, gry, fine-gr ss.		Kirtland	996'	
Fruitland	1555'	2108'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.		Fruitland	1555'	
Pictured Cliffs	2108'	2241'	Bn-Gry, fine grn, tight ss.		Pictured Cliffs	2108'	
Lewis	2241'	2731'	Shale w/siltstone stringers		Lewis	2241'	
Huerfanto Bentonite*	2731'	3108'	White, waxy chalky bentonite		Huerfanto Bent	2731'	
Chacra	3108'	3664'	Gry fn grn silty, glauconitic sd stone w/dk gry shale		Chacra	3108'	
Cliff House	3664'	3794'	ss. Gry, fine-grn, dense sil ss.		Cliffhouse	3664'	
Menefee	3794'	4384'	Med-dark gry, fine gr ss, carb sh & coal		Menefee	3794'	
Point Lookout	4384'	4808'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation		Point Lookout	4384'	
Mancos	4808'	5631'	Dark gry carb sh.		Mancos	4808'	
Gallup	5631'	6377'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh		Gallup	5631'	
Greenhorn	6377'	6434'	Highly calc gry sh w/chin lmst.		Greenhorn	6377'	
Graneros	6434'	6552'	Dk gry shale, fossil & carb w/pyrite incl.		Graneros	6434'	
Dakota	6552'	6906'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl chn sh bands clay & shale breaks		Dakota	6552'	

* Huerfanto Bentonite is the legal top of Mesaverde in New Mexico (North of Chacra line)