

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

FEB 2002

WELL API NO.

30-045-30955

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

B-11242-47 & V-4832

7. Lease Name or Unit Agreement Name

Ropco 17

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Richardson Operating Company #019219

3. Address of Operator

1700 Lincoln Street, Suite 1700, Denver, CO 80203

4. Well Location

Unit Letter O : 562 feet from the South line and 1392 feet from the East line

Section

17

Township

29N

Range

13W

NMPM

San Juan

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

5264 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

☐ PERFORM REMEDIAL ☐ PLUG AND ABANDON WORK☐ TEMPORARILY ☐ CHANGE PLANS ABANDON☐ PULL OR ALTER ☐ MULTIPLE CASING COMPLETION☐ OTHER:

SUBSEQUENT REPORT OF:

☐ REMEDIAL WORK ☐ ALTERING CASING☒ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT☒ CASING TEST AND CEMENT JOB☐ OTHER:

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1/15/02

MIRU Richardson. Drill and set 9 5/8" Conductor pipe to 20'.

1/24/02

MIRU L & B Speed Drill. Drill 8 3/4" to 135'. Circulate clean. POH w/ drill pipe. RIH w/ 7" casing. RU Cement crew, circ w/ H2O. Pump 65 sxs Class B w/3% cac12, 1/4" Cello Flake. Displace cement w/ 4 BBLS H2O. Cir 4 BBLS cement to surf. RDC, SDON. Casing set @ 133'.

1/25/02

Install Braden head. BOP 1000#. Drill 6 1/4" hole to 600'. Circ. POH w/ kelly. SDON.

1/26/02

Drill to 1160'. TD. POH w/ kelly. SDOWE.

1/28/02

POH laying down pipe. RUCC. RIH w/ 4 1/2" 10.5# ST&L csg. 1 jt 4 1/2" csg insert float 25 jts 4 1/2" casing. RDCC. Rucement. 70 sxs class B 2% 1/4# cello flake 12.5ppg. 70 sxs class 15.6PPG 1/4# cell fluke. Displace plug w/ 17.6 bbls H2O. Casing set @ 1132'. Float @ 1093. 5 BBLS cement to surface. RDMOL.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John WhislerTITLE OPERATIONS MANAGERDATE 2/1/2002

Type or print name

JOHN WHISLER

Telephone No. 303-830-8000

(This space for State use)

APPROVED

BY

TITLE

DATE

Conditions of approval, if any:

FEB - 6 2002