MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Initial I
Casing Wt. 1. I.B. 5.012 Set at 1776 Perf. 1885 To 1876
Casing Wt. 1. I.D. Set at 1976 Perf. 1887 To 1888
Tubing
Tubing
Tubing
Tubing
OBSERVED DATA ested Through Flow Data Flow Data Tubing Data Casing Data (Prover) (Choke) Press. Diff. Temp. Press. Temp. Press. Temp. Of Flow Calculations Size Size psig hw OF. psig OF. psig OF. Hr. FLOW CALCULATIONS Coefficient Casing Data OF. Press. Temp. Press. Temp. Of Flow Of F
CBSERVED DATA Type Taps Flow Data Flow Data Tubing Data Casing Data Choke) Press. Diff. Temp. Press. Temp. Press. Temp. Size Size psig hw OF. psig OF. psig OF. psig OF. FLOW CALCULATIONS FLOW CALCULATIONS Factor Fac
Flow Data Flow Data Flow Data (Choke) Press. Diff. Temp. Press. Temp. Press. Temp. Of Flow Calculations Factor Factor Factor Factor Factor Factor Factor Flow Calculations Flow Temp. Fress. Temp. Duration of Flow Calculations Flow Calculations Flow Calculations Flow Temp. Factor Factor Factor Factor Factor Fac
Flow Data (Prover) (Choke) Press. Diff. Temp. Press. Temp. Press. Temp. (Line) Size Size psig hw OF. psig OF. psig OF. psig OF. Hr. FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Factor Fact
(Prover) (Choke) Press. Diff. Temp. Press. Temp. Press. Temp. Of Flow (Line) Size Size psig hw OF. psig OF. psig OF. psig OF. Hr. FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow Factor
Size Size psig hw OF. psig OF. psig OF. Hr. I SMAIN 10 4000 FLOW CALCULATIONS Coefficient O. (24-Hour) The psig OF.
FLOW CALCULATIONS Coefficient $ \sqrt{h_w p_f} $ Pressure Flow Temp. Factor
FLOW CALCULATIONS Coefficient $ \sqrt{h_w p_f} $ Pressure Flow Temp. Factor
FLOW CALCULATIONS Coefficient $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow Factor Factor Factor Q -MCFPD Q -MCPD Q
Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow Factor Factor Factor Fpv Ppv Ppv Ppv Ppv Ppv Ppv Ppv Ppv Ppv P
(24-Hour) √h _w p _f psia F _t F _g F _{pv} @ 15.025 psi 12.365 40 1.000 0.606 1.000 475
12,365 40 1,600 0,9608 1,600 475
PRESSURE CALCUIATIONS
S Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas avity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid Gallery
wity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid 0. Pc Pc 465,12
P_{w} P_{t}^{2} $F_{c}Q$ $(F_{c}Q)^{2}$ $(F_{c}Q)^{2}$ P_{w}^{2} $P_{c}^{2}-P_{w}^{2}$ Cal. P_{w}
$ P_{t} (psia) $
8,8% A%,260 W
osolute Potential: MCFPD; n 0.65
MCFPD; h NOV 2 9 95 DDRESS DORESS
TNESSED
MPANY

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871. Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw= Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- $F_{\rm DV}^-$ Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_W cannot be taken because of manner of completion or condition of well, then P_W must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION TO ISSION

AZTS:

100. Co. 1 --- 3