NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	l	Rlane	3	**************************************	Fo	rmation	Mes	a Verde		County	Rio Ara	iba.
Init	tial_	xx		Annu	:21		Spe	cial		Date of	Test	6-12-57
								Rosa		We]	 1 No	20-14
								Purc	chaser N	et Connec	ted	
Casi	7 ing_5	5/8 3 N	/t	I	•D.	Set	36 t at 58	38 70 Pe	erf. 576	ot Connec	То	51.8
Prod	ducing	Thru:	Cas	sing		Tul	oing	хх	Type W	ell	ingle	
Date	e of C	omplet	ion:_			Packer	r	Sir	ngle-Brade Reserve	enhead-G. oir Temp.	G. or G	.0. Dual
								VED DATA				
Test	ed Th	rough	(PTG	**) (Choke)	(Heter)	s I	7 days		Type Tap	s	· · · · · · · · · · · · · · · · · · ·
				low D				Tubing		Casing D	ata 💮	
No.		over) ine)				Diff.	Temp.	Press	Temp.	Press.	Temp.	
	•	ize		ize	psig	h _w	$^{\mathrm{o}}\mathrm{_{F}}$.	psig	°F.	psig	[⊃] F•	of Flow Hr.
SI								1252		1250		
1. 2.			3/4	<u> </u>	205		170	205	720	061		3
3. 1		·	 		┼			 	 			
3. 4. 5.												
<u>5. l</u>												
No.	(:	effici 24-Hou		$\sqrt{h_{\mathbf{w}}}$	p _f r	ssure sia	Flow Fac		Gravity	Compre Facto Fpv	r	@ 15.025 psia
1. 2. 3. 4.		1605				217	.9896		.9000	1.080		2980
3 _e									· · · · · · · · · · · · · · · · · · ·			
4.												
as L ravi	ty of	Hydro Liqui	d Hydr	ocarb		PRE			Speci Speci	ific Gravi ific Gravi 54	ty Flow	ing Fluid
No.	P _w	osia)	Pt2	F	Q C	$(F_cQ)^2$	(F	(cQ) ² (-e-s)	673 P _w 2	$P_c^2 - P_w^2$	Ca:	
<u>;</u>									452.9	1144.8		1.40
1. 2. 3. 4.			., .				_				-	
4.											 	-
5.												
COMP	ANY_P	Potent:	North	west	Pipeline	e Corpor	MCFPD;		/ 1.2870		-	3
AGEN	T and	TITLE	C.	R. W	Farmir agner	We will be	At Test	Enginee	r	- 10	2. S.	6/11
WITN	ESSED_										7 7	VIA
COMP.	ANY						יייד כן	IARKS			0,00	
							n.e.M	C/III N			OR CO	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{L}}$.

•		E
OIL CONSERVAT	MON COMMIS	SION
AZTEC DIS	TRICT OFFICE	
No. Copies Rece	ived 2	
DISTR	HEUTION	
	NO PLONISHED	
Operator	The second secon	
Lights Fe	1	
From Ciffing	ار از این بیدهای میشود از این بیش این از از این برای این برای این برای این برای این برای این برای این این این این این این این این این ا	}
State of graden	The second secon	
10,5,95		
Transporter	· ·	
Street		-