

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Northwest Pipeline Corporation
3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 800' FNL & 990' FEL
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Spud, surface csg set


SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



5. LEASE
SF 078764
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Rosa Unit
8. FARM OR LEASE NAME
Rosa Unit
9. WELL NO.
#85
10. FIELD OR WILDCAT NAME
Blanco MV / Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 20, T31N, R5W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
N.M.
14. API NO.
30-039-22778
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6441' GR

NOTE: Report results of multiple completion of zone change on Form 9-331-C



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
7-2-81. Spudded 13-3/4" surface hole @ 2400 hrs.

7-3-81 Ran 9 jts (384') 10-3/4", 36#, K-55, ST&C Lone Star Steel csg set @ 388' KB. Woodco cmt'ed w/ 230 sx C1 "B" w/ 1/4# gelflake/sx & 3% CaCl₂. Displaced plug & down @ 0845 hrs 7-3-81. Circ 5 bbls cmt. WOC 12 hrs. NU Bradenhead & BOP. Tested to 600 psi. OK.

7-4-81 Drlg ahead to a depth of 950'.

7-5-81 Fishing for cones. Lost 3 cones from bit #2. TIH w/ magnet rec'd 1 cone.

7-6-81 Rec'd 2 cones from bit #2 w/ magnet. Drlg ahead to a depth of 2261'.

7-7-81 Drlg ahead to a depth of 2886'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE 7-7-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 9 1981

FARMINGTON DIST. 1

NMOCC