In Lieu Form	3160-5 DEPARTMENT OF	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993	
	SUNDRY NOTICES AND	D REPORTS ON WELLS deepen or reentry to a different reservoir. Use	5.	Lease Designation and Serial No. SF-078763	
"APPI	LICATION FOR PERMIT" for such proposals	deepen of rectary to a different reservoir.		If Indian, Allottee or Tribe Name	
	SUBMIT IN 1	RIPLICATE	7.	If Unit or CA, Agreement Designation ROSA UNIT	
1.	Type of Well ☐ Oil Well ☑ Signature	Other	8.	Well Name and No. ROSA UNIT #41A	
2.	Name of Operator WILLIAMS PRODUCTION COMPANY			API Well No. 30-039-25506	
3.	Address and Telephone No. PO BOX 3102 MS 37-4, TULSA, OK 74101 (913) 588-4592			Field and Pool, or Exploratory Area BLANCO MESAVERDE	
4.	Location of Well (Footage, Sec., T., R., M., or Survey Description) 2180' FSL & 1485' FEL, SEC 5, T31N, R05W			County or Parish, State RIO ARRIBA, NEW MEXICO	
	CHECK APPROPRIATE	BOX(s) TO INDICATE NATURE OF NOTICE, REP	ORT, OR	OTHER DATA	
	TYPE OF SUBMISSION	TYPE OF ACTION			
	□ Notice of Interior Subsequent Report □ Final Abandonment OHL, COLL, DOMEST 2	☐ Abandonment ☐ Recompletion ☐ Plugging Back ☐ Casing Repair ☐ Altering Casing ☑ COMPLETION OPERATIONS		☐ Change of Plans ☐ New Construction ☐ Non-Routine Fracturing ☐ Water Shut-Off ☐ Conversion to Injection ☐ Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
13.		Clearly state all pertinent details, and give pertinent date locations and measured and true vertical depths for all			
6-13-9 5555'.	TOC @ 5891' KB. Drill out cement to 5921' KB FT csg to 3300 psi. held-O.K. Spot 500 gal of 1 5558', 5561', 5564', 5570'. Total of 11 shots. Pum	3. .5% HCl @ 5605'. Perforate Point Lookout w/ 3-1/8" gu ped 1000 gal of 15% HCl w/ 22 balls. Good ball action RU Petro Wireline and perforate Point Lookout w/ 3-1/8"	and total	ball-off to 3400 psi.	

5453', 5485', 5507', 5510', 5513', 5516', 5519'. Total of 28 (0.37" dia.) holes. BJ established a rate of 17.5 BPM at 1750#. Dropped 60 balls in 1000 gal of 15% HCl. Good ball action and balled off to 3300#. Recovered 45 balls with 26 hits. Fraced well with a 61,500# of 20/40 sand at 1 - 2.5 ppg. Job completed at 1900 hrs 6/15/95. ISIP = 760#, 15

5624, 5630', 5633', 5665', 5668', 5680', 5694', 5703', 5709', 5745', 5773', 5793', 5799', 5815', 5825', 5830', 5842', 5851', 5860', 5892', 5899'. Total of 24 holes.

6-22-95 Pitot guages: 0745=354 MCF, 0800=354 MCF, 0815=331 MCF, 0830=331 MCF. 1300 hrs = 408 MCFD, 1345 hrs=360 MCFD. 6-23-95 Pitot guage. 30 min. = 470 MCF, 60 min. = 345 MCF. TIH

min. = 480#. ATP = 2450#, AIR = 62 BPM, MTP = 3100#, MIR = 63 BPM. Total fluid = 1962 bbls.

6-24-95 Set cement retainer at 5524'. TIH with 174 jts. (5467.27') of 2-3/8", 4.7#, J-55, EUE tubing and landed at 5479'KB with notched collar on bottom and SN on top of bottom joint. Rig released at 0700 hrs.

6-15-95 Dropped 80 balls in 1000 gal of 15% HCl. Complete ball off. Recovered 55 balls with 37 hits. Fraced Point Lookout with a 30,500 gal pad of slick water, followed by 80,000# of 20/40 sand at 1 - 2.5 ppg (estimated due to densiometer failure). Job completed at 1027 hrs 6/15/94. ISIP = 630#, 15 min. = 440#. ATP = 2000#, AIR = 70 BPM, MTP = 2500#, MIR = 72 BPM. Total fluid = 2390 bbls. Set CIBP at 5527'. Pressure tested plug and casing to 3300# - OK. Spotted 500 gal of 15% HCl across perfs. TOH. Perforated Menefee/ Cliffhouse at 5289', 5291', 5328', 5342', 5365', 5367', 5369', 5371', 5378', 5380', 5382', 5384', 5386', 5388', 5390', 5392', 5394', 5396', 5398', 5427', 5433',

14.	I hereby certify that the foregoing is true and correct Signed SUSAN GRIGUHN	Title	CLERK	Date <u>July 11, 1995</u>
	(This space for Federal or State office use)	itle	Date	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

ACCEPTED FOR RECORD

JUL 20 1995

FARMINGTON DISTRICT OFFICE 933