



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

Delhi Oil Corporation 1315 Pacific Avenue Dallas, Texas
State _____ Well No. 1 in SW 1/4 of Sec. 32 T. 30-N
R. 9-W, N. M. P. M., Blanco Field, San Juan County.
Well is 990 feet North of South line and 990 feet East of West line of Station 32
If State land the oil and gas lease is No. _____ Assignment No. _____
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is _____ Address _____
Drilling commenced 3/30 19 51 Drilling was completed 4/23 19 51
Name of drilling contractor San Juan Drilling Co. Address Farmington, New Mexico
Elevation above sea level at top of casing 5735 feet. D.F.
The information given is to be kept confidential until Not confidential 19 _____

OIL SANDS OR ZONES

No. 1, from 2302 to 2355-G No. 4, from _____ to _____
No. 2, from 3924 to 4686-G No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED TO	PURPOSE
10 3/4	49.50	8RT	Spang	252	Non.	---	---	Surface Pipe
7	20-J	8RT	"	2933	Baker	---	---	Long String
7	20-H	8RT	"	10W	---	---	---	" "
2	4.70	8RT	Natl.	4019	---	---	---	---

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10 3/4	260	150	Hallib.	Drilled W/ water		
8 3/4	7"	3933	"	9.8		
2	4014	---	---	---	---	

PLUGS AND ADAPTERS

Heaving plug—Material None Length _____ Depth Set _____
Adapters—Material None Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
Qts.	Tin	Sng.	2060	6/28/51	3993-4827	4410-4485

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4824 feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing Well shut in 9/5/51 19 _____
The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be. _____
If gas well, MCF per 24 hours 1860 Gallons gasoline per 1,000 cu. ft. of gas unknown
Rock pressure, lbs. per sq. in. 870

EMPLOYEES

T. C. Russell Driller T. Glazebrook Driller
J. Parker Driller H. Young Pusher

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Farmington, New Mexico Sept. 25, 1951
Name J. B. Howell
Position J. B. Howell—Superintendent
Representing Delhi Oil Corporation
Address P. O. Box 1175

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	472	472	Sandy to sandy shale with thin beds of sand.
472	558	86	Coarse sand with thin beds of shale.
558	745	187	Sandy to sandy variegated shales with thin beds of sand.
745	895	150	Massive beds of coarse grain sandstone with thin beds of sandy shale.
895	935	40	Wavy variegated shales.
935	1030	95	Interbedded sandstone and hard sandy shales.
1030	1088	58	Sandy to sandy shales.
1088	1236	148	Massive beds of coarse grain, porous sandstone.
1236	1966	730	Hard, sandy, green to brown, variegated shales with local lenses of soft sandstone, contain slight amounts of gas. Top of Kirtland--1236.
1966	2302	336	Interbedded coal, sandstone and carb. shale. Top of Fruitland--1966.
2302	2355	53	Coarse grain, white, slightly porous sandstone. Top of Pictured Cliffs--2302.
2355	3924	1569	Sandy to wavy gray shales. Top of Lewis--2355.
3924	4020	96	Sandstone, coarse, porous, containing light amounts of gas. Top of Cliff House--3924.
4020	4573	553	Interbedded coal, sandstone and shale. Top of Menafes Formation. 4020.
4573	4686	113	Sandstone, coarse, porous, soft, containing varying amounts of gas. Top of Point Look-out. 4573.
4686	4824	138	Sandy shale--Top of Menafes--4686.

NOTE--WELL DRILLED WITH GAS BELOW 7" CASING SEAT.