

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

Form C-101
Revised (12/1/55)

NOTICE OF INTENTION TO ~~DRILL~~ DEEPEN

Notice must be given to the District Office of the Oil Conservation Commission and approval obtained before drilling or recompletion begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in QUINTUPLICATE. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission. If State Land submit 6 Copies Attach Form C-128 in triplicate to first 3 copies of form C-101

Durango, Colorado
(Place)

7-9-65
(Date)

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Gentlemen:

Drilling

You are hereby notified that it is our intention to commence the ~~Drilling~~ of a well to be known as

Tenneco Oil Company

(Company, or Operator)

State

(Lease)

Well No. #1

M

(Unit)

The well is

located 990' feet from the South line and 990' feet from the

West

line of Section 32, T. 30N, R. 9W, NMPM.

(GIVE LOCATION FROM SECTION LINE) Blanco MV & Basin Dakota Pool, San Juan County

If State Land the Oil and Gas Lease is No. B-10870

If patented land the owner is

Address

We propose to drill well with drilling equipment as follows: Rotary

The status of plugging bond is

Drilling Contractor

We intend to complete this well in the Dakota & M.V. (Dual)

formation at an approximate depth of Approximately 7886 feet.

CASING PROGRAM

We propose to use the following strings of Casing and to cement them as indicated:

Size of Hole	Size of Casing	Weight per Foot	New or Second Hand	Depth	Sacks Cement
6-1/4"	4-1/2"	11.6# & 10.5#	New	7886	1st stage 150 sx
					2nd stage
					Sufficient to
					circulate to surface

If changes in the above plans become advisable we will notify you immediately.

ADDITIONAL INFORMATION (If recompletion give full details of proposed plan of work.) Rig up and set 7" drillable packer in 7" and squeeze open hole with 350 sx Class "A" cmt, 12 1/2" gilsonite, and 100 sx "A" 15% sand cement. Drill with 3" knuckle joint to Dakota zone to approximately 7886'. Log and run 4 1/2" casing, cement in 2 stages. First stage T.D. to 500' above top of Mesaverde. Second stage circulate cement from 500' above Mesaverde to surface. Perf and frac Dakota and Mesaverde. Set model "D" packer above Dakota and complete as dual. Conduct deliverability test & packer leakage test.

Approved
Except as follows:

Subject to approval of intentional deviation.

OIL CONSERVATION COMMISSION

By *A. R. Kendrick*

Tenneco Oil Company

(Company or Operator)

Original Signed By:

By J. H. WATKINS

Position District Office Supv.

Send Communications regarding well to

Name Tenneco Oil Company

Address Box 1714, Durango, Colorado