UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

SUBMIT IN TRIPLICATE*

Form approved.

_		Budget	Bures	tu N	o. 42–R	.147
5.	LEASE	DESIGN	ATION	AND	SERIAL	NØ.

GEOLOGICAL SURVEY								
SUNDRY	NOTICES	AND	REPORTS	ON	WELLS			

SF 078107 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

(Do not use this form for propos Use "APPLICA	als to drill or to deepen or plug back to a different reservoir. TION FOR PERMIT—" for such proposals.)	,	- 7.
I. OIL GAS WELL X WELL OTHER		7. UNIT AGREEMENT N	AMB
2. NAME OF OPERATOR	•	8. FARM OR LEASE NA	ЖB
Sunray DX Oil Company		N. M. Federal	L "L"
3. ADDRESS OF OPERATOR		9. WELL NO.	
P. O. Box 1416, Roswell	, New Mexico	1	•*
 LOCATION OF WELL (Report location of See also space 17 below.) At surface 	10. FIELD AND POOL, OR WILDCAT Undesignated		
		11. AUC., T., R., M., OR SURVEY OR ARE	
790' FNL & 790' FWL	Sec 29, T-30	-N, R-15-W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARIS	H 13. STATE
	5324' DF	San Juan	New Mexico
16. Check Ap	propriate Box To Indicate Nature of Notice, Report, or	Other Data	

NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ARANDON* REPAIR WELL CHANGE PLANS (Other)

SUBSEQUENT REPORT OF: WATER SHUT-OFF REPAIRING WELL FRACTURE TREATMENT ALTERING CASING SHOOTING OR ACIDIZING ARANDON MENT® (Other) Plug and Abandon

(Nore: Report results of multiple completion on Well Completion or Recompletion Report and Log form.): 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones p nent to this work.) *

- Loaded hole w/mud.
- Cut off 5 1/2' csg @ 3320'. Pulled production csg. Kept hole loaded w/mid 2.
- Set 35 sx cmt plug (3880'-4240') to cover perfs. 3.
- Set 12 sx cmt plug in and out of 5 1/2" stub (3290'-3350'). 4.
- Set 17 sx cmt plug in and out of 8 5/8" surface csg (380'-440'). 5.
- Set 10 sx cmt plug @ surface. 6.
- 7. Installed dry hole marker.
- Removed surface equipment and cleaned up location. 8.

that the for going is true and correct TITLE District Engineer May 16, 1967 🕰n Hastings DATE (This space for Federal or Sta APPROVED BY DATE tibba ni 3 padu 14 padu 15 padu CONDITIONS OF APPROVAL, IF ANY: