•	
Form 9-331 5 BLM 1 File	Form Approved.
Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 080508A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
debeodione solve!	- The state of the order of the
COMPRES NOTICES AND DEPORTS ON WELLS	7 LINIT ACRECMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a differen reservoir, Use Form 9-331-C for such proposals.)	
reservoir, Use Form 9-331-0 for such proposals.	8. FARM OR LEASE NAME
1. oil gas Dan	PAF 以事務的 E Sign
well well other P & A	9. WELL NO. 1996 - 1997
2. NAME OF OPERATOR	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
DUGAN PRODUCTION CORP.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Horseshoe Gallup - 電音量
P O Box 208, Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	<del></del> 1
below.)	Sec. 19, T30N, R15W
AT SURFACE: 1980' FNL - 660' FWL	12. COUNTY OR PARISH 13. STATE 3
AT TOP PROD. INTERVAL:	San Juan 388 NM
AT TOTAL DEPTH:	14. API NO. ** \$ 7 \$ = 2.05 0
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	
REPORT, OR OTHER DATA	
Heroni, on onle on	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	
TEST WATER SHUT-OFF []   DECEN	
FRACTURE TREAT	
SUCCE OF ACIDIZE TO	
REPAIR WELL (NOTE: Report results of multiple completion or zone	
PULL OR ALTER CASING	
ABANDON* □ M.	
(other)	UST, 3
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and	
measured and true vertical depths for all markers and zones pertinent to this work.)*	
This well was plugged in the following manner:on 3-3-83క్ష్మ్ క్షేష్ట్ క్షేహ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ్హ	
그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	
1. Spotted 18 sk cement plug (21.24 cu.ft.) from 2295 to 2140 2 5 5 5	
2. Found free point of casing and shot $5\frac{1}{2}$ casing off at $21,11$	
3. Spotted 17 sk cement plug (20 cu.ft.) from 2140' to 2040'. 資 資富	
4. Spotted 30 sx cement plug (35.4 cu.ft.) from 1420-to 1315' (Note: 13	
this plug is 50' below and 50' above Cliff House top.	
5. Spotted 15 sk cement plug (17.7 cu.ft.) from 124 to 75.	
	notice when surface equipment is
removed.	
*Note - left 9.2# per gal. mud between all plugs. 그림을 그는 경우 등	
Subsurface Safety Valve: Manu. and Type Ft.	
18. I hereby certify that the foregoing is true and correct	
Geologist	3-4-83- 7 P 4-33
SIGNED // Jim L. Jacobs	DATE
(This space for Federal or State of	APPROVED

APPROVED BY CONDITIONS OF APPROVAL IF ANY:

Approved as to plugging of the well bore.

Liability under bond is retained until surface restoration is completed.

MMOCS

\*See Instructions on Reverse Side

M. MILLENBACH
AREA MANAGER