

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRILL ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☒ DEEP EN ☐ PLUG BACK ☐ DIFF. REVR. ☐ Other ☐
OCT 10 1985

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1750'N, 1650'E

At top prod. interval reported below

At total depth

OIL CON. DIV.
DIST. 3
RECEIVED
OCT 04 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO. DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.

SF 077764

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Schumacher

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC. T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 17, T-30-N, R-10-W
NMPM

12. COUNTY OR PARISH
San Juan

13. STATE
NM

15. DATE SPUDDED 8-31-51 16. DATE T.D. REACHED 9-17-85 17. DATE COMPL. (Ready to prod.) 9-30-85 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6434' GL 19. ELEV. CASINGHEAD 6434'

20. TOTAL DEPTH, MD & TVD 5812' 21. PLUG. BACK T.D., MD & TVD 5797' 22. IF MULTIPLE COMPL., HOW MANY* One 23. INTERVALS DRILLED BY Rotary 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 5304-5661' (Blanco Mesa Verde) 25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN
Cased Hole Comp. Neutron Log; Temp Surveys

27. WAS WELL CORED
No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
10 3/4"	30.0#	250'	12 1/4"	150 cu ft	
7"	20.0#	5111'	8 3/4"	200 cu ft	
4 1/2"	10.5#	5812'	6 1/4"	270 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	5607'	

31. PERFORATION RECORD (Interval, size and number)

5487, 5492, 5500, 5503, 5506, 5520, 5533, 5558, 5566, 5574, 5603, 5610, 5617, 5630, 5661 w/1 SPZ. 2nd stage 5304, 5308, 5312, 5316, 5320, 5324, 5328, 5332, 5336, 5340, 5345, 5350, 5355, 5358, 5375, 5379, 5383, 5416, 5454, 5460 w/1 SPZ.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5487-5661	58,000# 20/40 sand&81,200 gals wt
5304-5460	46,000# 20/40 sand&97,200 gals wt

33. PRODUCTION

DATE FIRST PRODUCTION 9-22-85		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing				WELL STATUS (Producing or shut-in) Shut in	
DATE OF TEST 9-30-85	HOURS TESTED 3 Hrs.	CHOKE SIZE 3/4"	PROD'N. FOR TEST PERIOD →	OIL—BBL. 0	GAS—MCF. 144 MCF	WATER—BBL. 0	GAS-OIL RATIO 0
FLOW. TUBING PRESS. SI 870	CASING PRESSURE SI 875	CALCULATED 24-HOUR RATE →	OIL—BBL. 0	GAS—MCF. 1248	WATER—BBL. 0	OIL GRAVITY-API (CORR.) 0	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Shut in to be Sold

TEST WITNESSED BY

Gabe Archibeque

35. LIST OF ATTACHMENTS

Temp Surveys

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Drilling Clerk

DATE

OCT 08 1985

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	1650'	1767'	ss. White cr-grn s.	Ojo Alamo Kirtland Fruitland Pic.Cliffs Cliff House Menefee Point Lookout Mancos	1650'	
Kirtland	1767'	2608'	Gry sh interbedded w/tight gry fine-grn ss.		1767'	
Fruitland	2608'	3005'	Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.		2608'	
Pictured Cliffs	3005'	4600'	Gry, fine-grn tight, varicolored soft ss.		3005'	
Cliff House	4600'	4792'	ss. Gry, fine-grn, dense sil ss.		4600'	
Menefee	4792'	5287'	Gry, fine-grn s, carb sh & coal	Point Lookout Mancos	4792'	
Point Lookout	5287'	5787'	Gry, very fine sil ss w/frequent sh breaks		5287'	
Mancos	5787'	5812'	Gry carb sh.		5787'	