



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078316
Unit Florence Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 20, 1960

Well No. 2-16 is located ¹⁰¹⁰~~990~~ ft. from [N] line and 990 ft. from [E] line of sec. 6

NE 1/4 Sec. 6 (1/4 Sec. and Sec. No.) T-35-N (Twp.) R-9-W (Range) N.M.P. (Meridian)
Blanco (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 5374.9 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogs, cementing points, and all other important proposed work)

T. D. of hole 635', 258' of 10-3/4" set at 270' with 225 sacks of cement. 12 Drill collars were lost in hole and extended 15' up in the surface casing. Bottom plug of cement from 270' to 220' with 25 sacks cement; Rotary and left in casing, 25' plug with 15 sacks cement from 25' depth to surface. A 10' length of 4" pipe was set 5' in cement below surface and 4' above ground level.

(Report filed as per your request of 1/19/60.)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blanco Gas Company

Address P. O. Box 1175

Hamilton, New Mexico

By J. B. Howell

Title District Superintendent

