

(June 1993)

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir. USE "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Vantage Point Operating Company (713) 780 -1952

3. Address and Phone No.

2401 Fountain View Drive, Houston, Texas 77057 - 4862

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

380' FSL & 2280' FEL, Sec 3, T30N, R16W, NMPM

5. Lease Designation & Serial No.: SF-081226-B

6. If Indian, Allottee or Tribe Name:

Federal

7. If Unit or CA, Agreement Designation:

Horseshoe Gallup Unit

8. Well Name & No.: Horseshoe Gallup Unit # 258

9. API Well No.: 3004509811

10. Field and Pool, or Exploration Area:  
Horseshoe Gallup

11. County or Parish, State  
San Juan County, New Mexico

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form)

TYPE OF ACTION

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8 5/8" csg @ 75'RKB PBSD @ 1690' Perforations @ 1535'- 1570'  
1640'- 1670'

It is proposed to P&A this well due to collapsed casing at 450'. The proposed procedure is to spot cement across the perforations from 1690' to 1485'. Tag the plug after 2 hrs. Spot another cement plug from 1485' to 150'. Perforate a hole at 150' and establish an injection rate thru the hole at 150' and cement from 150' thru the bradenhead and leave cement from 150' to surface in the casing.

RECEIVED  
JUN 14 1993  
OIL CON. DIV.  
DIST. 3

RECEIVED  
BLM  
93 JUN -4 AM 11:38  
070 FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct

Signed

Consulting Engineer for

Title Vantage Point

Date 6/11/93

(This space for Federal or State office use)

Approved by

Title

APPROVED

JUN 09 1993

Date

DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.