

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

5-00
1-JH Hampton
1-HLKendrick
1-F

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name	
2. Name of Operator Beta Development Co.		8. Farm or Lease Name Rhoda Abrams	
3. Address of Operator 125 Petroleum Club Plaza, Farmington, N.M.		9. Well No. 1	
4. Location of Well UNIT LETTER P , 910 FEET FROM THE South LINE AND 990 FEET FROM THE East LINE, SECTION 5 , TOWNSHIP 30N , RANGE 11W NMPM.		10. Field and Pool, or Wildcat Basin Dakota	
15. Elevation (Show whether DF, RT, GR, etc.) 5754' GL		12. County San Juan	

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>


SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon, as follows:

Load hole w/water, circulate out mud, shale & sand to T.D. 6801'. Spot 50 sx cement in bottom to cover all Dakota casing perforations; pull tbg up hole & pump in 15 sx cement to base of Point Lookout 4730'; 15 sx plug top of Menefee 3995'; 15 sx plug top of Pictured Cliffs 2203'. Perf. 4-1/2" csg base of Ojo Alamo 997', pump in 25 sx & try to squeeze outside csg; put 10 sx in surface pipe w/marker.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original signed by:

D. E. BAXTER

SIGNED _____ TITLE **Superintendent** DATE **November 26, 1969**

APPROVED BY *Ernest Ames* TITLE *Supt Dist III* DATE *12-1-69*
CONDITIONS OF APPROVAL, IF ANY: