



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 081226-B
Unit Bolack

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<p>JUL 15 1957</p> <p>U. S. GEOLOGICAL SURVEY</p> <p>FARMINGTON, NEW MEXICO</p>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Subsequent Report of Sand-Oil</u>	
	<u>Treatment</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 15th, 1957

Well No. 2 is located 1920 ft. from N line and 350 ft. from W line of sec. 3

NW/4 SW/4 Sec. 3 30N 16W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Unnamed San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5447 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 6-26-57 TD 1463'. Cleaned out to 1419'. Perforated 1265-1305' and 1376-1400' with 4 holes per foot. Sand-oil treated with 1,258 barrels of oil and 60,000# sand, flushed with 42 barrels of oil. Dropped 177 neoprene-coated nylon balls during treatment. Average injection rate 50.4 barrels per minute.
- 6-29-57 Swabbed out free oil. Sand-oil treated with 660 barrels of oil and 25,000# sand, flushed with 180 barrels of oil. Dropped 190 neoprene-coated nylon balls during treatment. Treating pressure 800-900#, average injection rate 76.6 barrels per minute. Before treatment well swabbed at rate of 20 BOPH. After treatment flowed at rate of 60 BOPH.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company TOM BOLACK

Address 1010 North Dustin

Farmington, New Mexico

By Tom Bolack
Title _____