Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Evniros: March 31 1003

5. Lease Designation and Serial No. BUREAU OF LAND MANAGEMENT 14-20-603-2021 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Navaja Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Gas Well Other 8. Well Name and No. Joella 2. Name of Operator King Oil % NMGCD 30045-10027 3. Address and Telephone No. 1000 Rio Erazos KO 10. Field and Pool, or Exploratory Area AZTEC, NM 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 5-30N-17W 11. County or Parish, State 9901Na 990/E NM San Juan CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all perment details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work is King Oil Company, Joella #2, A-05-30N-17W, 30-045-10027 Cleaned off location, dug pit, set anchors and worked on road. 12-17-96 Rigged up BOP and PU four drill collars and one joint of 2 3/8 tbg. Tagged up at 160' and continued to drill junk in hole. POH with collars and checked bit; wear was 12-23-96 in the center of bit. WIH with impression block and determined the csg. was collapsed or parted at 160'. WIH with 2 3/8 tbg. and went through parted csg. and tagged up at TD (760'). 12-24-96 Circ. hole and noticed fluid loss. Circ. hole with class B cement and celloflake with 90 sxs. WOC and cement fell back. Circ. cement to the surface with 45 sxs; total of 135 sxs used. Installed dry hole marker, removed anchors, covered pit and leveled location. Plugged NMOCD Approved by \_\_\_\_\_\_ Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.