STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer-leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

		KWOOD & N	ICHO	LS COMP	ANY_Lease	NORTH	EAST E	BLANCO I	UNIT	Well _No. <u>56</u>
Location of Well:		Sec34	Г w p	31N	Rge	7W		County	SAN	JUAN
	NAME OF RESERVOIR OR POOL				TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art. Lift)			PROD. MEDIUM (Tbg. or Csg.)
Upper Completion		MESAVER	DE		GAS		FLOW			CASING
Lower Completion		DAKOTA	4		GAS		FLOW			TUBING
			PF		SHUT-IN PR	ESSURE D	ATA			
Upper Completion	9/12/95 10:30			Length of time shut-in 5 DAYS		SI press. psig	SI press. psig 360		Stabilized? (Yes or No) YES	
Lower Completion	Hour, date shut-in 9/12/95 10:30			Length of time shut-in 5 DAYS		SI press. psig	SI press. psig 550		Stabilized? (Yes or No) YES	
··				FL	OW TEST N	O. 1				
Commenced at (hour, date)* 9/17/95 10:30					Zone producir	Zone producing (Upper or Lower)		LOWER		
TIME (hour,date)		LAPSED TIME SINCE*	PRESS Upper Completion		URE Lower Completion		PROD. ZONE TEMP.		REMARKS	
9/17/95 10:30		0 DAYS		360	550					
9/18/95 10:30		1 DAY	360		410					
9/19/95 10:30		2 DAYS		360 360						
- 					······································	ļ		·		
						<u> </u>				
	n rate du									
Oil: Gas:		BOF	D bas	sed onMCF1	Bbls. i PD: Tested th		Hours or Met		METER	GOR
			MI		HUT-IN PRE			,		
Upper Completion	lour, date shut-	in		ength of time shut-in		SI press. psig			Stabilized? (Yes or No)	
Lower -	1 '			Length of time shut-in		SI press. psig	SI press. psig		Stabilized? (Yes or No)	
				· . ·		_				

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date	te) 本中		Zone producing (Upper or Lower):						
TIME (hour, date)	LAPSED TIME	PRES Upper Completion	SURE Completion	PROD. ZONE TEMP.	REMARKS				
(11001) 0010)	J. C. T.	Opper Completion	Completion	IEMF.					
					_				
Production rate du	ring test								
Oil:	BOPI	based on	Bbls. in	Hours.	Grav GOR				
Gas:		MCFF	D: Tested thru	(Orifice or Meter)					
Remarks:				· · · · · · · · · · · · · · · · · · ·					
· - <u></u>									
I hereby certify tha	it the informatio	n herein containe	d is true and cor	nplete to the best	of my knowledge.				
Approved	Johnny Rol	insen	. 19 O	perator B	lackwood & Nichols Company				
New Mexico Oil	Conservation Di DEC 1 1	vision		AL	Δ				
Зу	DEPUTY OIL & GAS		Ti	tieD	istrict Superintendent				
Tidel	DELOTT OIL & GAS	PINOPEUIUN	D:	21eD	ecember 4, 1995				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture recatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distructed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).