## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool	Manes 1	Seaster	<u>40</u>	Fo	rmation	Mag	PEVERÃO	<del></del>	_County_	Sen .	Page .	
Initi	ial		_Annual			Spec	ial		_Date of	Test_	hely 1	5,1960
Compa	ny Black	tweed A	Hi che	ls Con	per l	Lease1	erthess	Blance	<b>Und t</b> We	Ll No	59-2	<u> </u>
Unit	<u> </u>	Sec	<b>♣</b> _Twp↓	311	Rge		<b>√</b> Purc	haser <u>I</u>	Pase Het	ural de	e Co.	
Casin	ig W	t. 13.	<b>50</b> I.D	. 4.5	<b>50</b> Set	at	<b>981.</b> Pe	rf <b>550</b>	21	To	18281	
Tubin	ig <b>2-3/1</b> W	t. 4.7	I.D		Set	at_ <b></b>	Pe	rf. 375	51	To	767	
Gas F	ay: From_	5502	To_ <b>50</b>	28	L	x	G			Bar.Pr	ess	11.5
	cing Thru:						1	Type We	:11	عد		
	of Complet						Sin	gle-Brade	enhead-G.	G. or		
	-				_		ED DATA	<del></del>	• •			
Teste	d Through	(Press	⊯r) (Ch	oke)	(Motar)	<b>V</b>			Type Tap	16		
			ow Dat				Tubing	Dat a	Casing I		<del>-</del> -	
N.	(Prover)	(Chok	ce) P		Diff.	Temp.						
NO.	(Line) Size	Siz	se	psig	h <sub>w</sub>	°F•	psig	° <sub>F</sub> .	psig	°F.		of Flow Hr.
SI 1.		3/4	20				1120		1120			
2.							193		560	<u> </u>		3 Res
3 <b>.</b>										<del> </del>	<del> </del>	
5.												
<del></del>		<del></del>					CULATION				·· <u>·</u>	
No.	Coeffici			_		Fac	tor	Factor	Compre	· ~	$\cap$ _MC	of Flow FPD
	(24-Hou	r) 7	/ hwpf			F	t	F <sub>g</sub>	Fpv			
1. 2. 3. 4.	12,3659				04						25	22
3 e				-								
5.				工								
					PRE	SSURE CA	ALCU ATI	ONS				
as Li	quid Hydro	carbon	Ratio_			cf/bbl.	4	Speci	fic Gravi	ty Sepa	arator	Gas
	y of Liquid	d Hydro		s		deg.		Speci Pc-	fic Gravi	ty Flow	ving F	luid
·						<u>-</u>	~,	- c		c		
	$P_{\mathbf{w}}$	52	7 2 2		(2.0)2	(2)	0)2		p <sup>2</sup> p <sup>2</sup>	$T_{\alpha}$	,	<b>.</b>
No.	Pt (psia)	$P_{\mathbf{t}}^{2}$	F <sub>c</sub> Q		$(F_cQ)^2$	(1.	cQ) <sup>2</sup> -e <sup>-s</sup> )	$P_{w}^{2}$	$P_c^2 - P_w^2$	l Ca	al.	Pw Pc
			1					325	253			
3.								<del></del>			_ i	
1. 2. 3.							1			<del></del>		
	ute Potent	ial•		 L3		MCRPD.	n					
COMPA	NY				pergr	,			<del></del>			
ADDRE AGENT	SS pa	Box 12	riginal Sig	ned G	, Colem			Con and -	bandan *		<del></del> ,	
WITNE:	SSED		DeLasso I		306	1530 LOC	me id	Superin'				·
COMPA	NY				·	DES	ARKS			SOFI	PR	
						n.e.pu	uimo			13.11s	AED	\

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- P<sub>c</sub>= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw- Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P<sub>f</sub> Meter pressure, psia.
- hw Differential meter pressure, inches water.
- $F_g \subseteq Gravity$  correction factor.
- $F_t$  Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .

STATE OF N	EW MEX	ICO	
OIL CONSERVATION	N COM	MISSIO	1
AZI C DIST	CT OF	IÇE	
NUMBER OF COPIES REC	CSVI	é	2
D:ST1.	S. ON		
SANTA FE		7 L	
FILE		7	
U.S.G.S.		7	
LAND OFFICE		r	
	GAS -		
PROKATION OFFICE	_		
OPERATOR	_		