

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1790' FNL, 1790' FEL, Sec. 14, T-31-N, R-9-W, NMPM

5. Lease Number
SF-078505

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Seymour #8

9. API Well No.
30-045-10758

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Pay add and restimulation	

13. Describe Proposed or Completed Operations

6-6-96 (Contacted 599-0615, Farmington BLM to notify Drake #24 will move on location and may flare @ 9:30 a.m. 6-6-96).

6-12-96 MIRU. ND WH. NU BOP. Tbg stuck. TIH, ran CCL & free point. Chemical cut tbg @ 5630'. TOO. TIH w/fishing tools. TOO. w/fish & fishing tools.

6-13-96 TIH w/5 1/2" csg scraper to 5760'. Drill float collar. TOO. One cone came off bit. TIH w/RBP, set @ 5154'. TOO. Load hole w/1% Kcl wtr. TIH w/pkr, set @ 62'. PT csg & RBP to 3000 psi/15 min, OK. TOO. w/pkr. TIH w/retrieving tool, Release RBP, TOO. TIH w/magnet & mill. Work magnet on bottom.

6-14-96 Mill on junk. Drill cmt to shoe @ 5790'.

6-15-96 Blow well clean. TOO. w/magnet & mill. TIH, blow well & CO. Drill from 5790' to new TD @ 6050'. Blow well clean.

6-16-96 Blow well & CO. TOO. TIH, ran logs. TOO. TIH, blow well & CO. TIH w/12 jts 3 1/2" FL4S EUE lnr, set @ 6037'. Top of lnr @ 5755'.

6-17-96 Cmt d w/3 bbl 50/50 poz w/0.3% Halad-344, 0.25 pps Flocele, 3 pps Gilsonite. Displace w/52.5 bbl wtr. WOC. TIH, tag TOC @ 6020'.

6-18-96 Ran CBL-CCL-GR @ 5580-6023', TOC @ 5790' in logged interval. TOO. PT 3 1/2" csg to 5000 psi/15 min, OK. TIH, spot 100 gal 15% Hcl. TOO. Perf lower Point Lookout w/2 SPF @ 5823, 5838, 5845, 5849, 5854, 5870, 5875, 5881, 5891, 5901, 5910, 5915, 5932, 5936, 5940, 5960, 6003, 6006' w/36 holes total. Frac lower Point Lookout w/8000# 40/70 sd, 53,000# 20/40 Arizona sd, 10,000# 20/40 Resin coated sd, 547 bbl 20# x-link gel. CO after frac.

Continued on back

14. I hereby certify that the foregoing is true and correct.

ACCEPTED FOR RECORD

Signed Nancy Oltmanns for Title Regulatory Administrator Date 7/9/96

JUL 12 1996

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date _____

CONDITION OF APPROVAL, if any: _____

FARMINGTON DISTRICT OFFICE
BY 221

NMOCD

6-19-96 TIH, tag sd @ 4670'. CO to 5250'. TOOH. Pump 100 bbl 1% Kcl wtr down annulus. TOOH.
 6-20-96 TIH, CO to 3 1/2" lnr top @ 5755'. Blow well clean. TOOH. TIH w/RBP, set @ 5750'.
 TOOH. TIH w/5 1/2" FB pkr, set @ 5735'. PT RBP to 3000 psi/15 min, OK. Release pkr,
 TOOH. TIH w/pkrs, set bottom pkr @ 5336', set top pkr @ 5158'. Load annulus. PT top
 pkr to 2000 psi, OK. Swab well. TIH to retrieving standing valve. Cannot latch.
 6-21-96 TOOH. TIH, latch back onto scab lnr. Latch standing valve, TOOH. TIH w/pkr, set @ 63'
 Frac existing Menefee/Point Lookout @ 5436-5720' w/885 bbl 20# & 30# x-link gel.
 100,000# 20/40 Arizona sd & 20/40 Resin coated sd. Latch lnr, TOOH w/lnr. TIH w/RBP
 set @ 5400'. TIH w/pkr, set @ 5350'. PT RBP to 3000 psi, OK. TOOH w/pkr. Frac
 existing Cliff House perfs @ 5204-5300' w/651 bbl 20# x-link gel, 80,000# 20/40
 Arizona sd & 20/40 Resin coated sd.
 6-22-96 CO after frac. TOOH. TIH w/retrieving tool, blow well & CO.
 6-23-96 Blow well & CO.
 6-24-96 Blow well & CO. Latch RBP @ 5400', TOOH. TIH, blow well & CO.
 6-25-96 Blow well & CO.
 6-26-96 Blow well & CO. Latch RBP @ 5750', TOOH. TIH, blow well & CO.
 6-27-96 Blow well & CO. TOOH. TIH w/12 jts 1 1/2" 2.9# J-55 10RD EUE tbg & 179 jts
 2 3/8" 4.7# J-55 8RD EUE tbg, landed @ 5995'. ND BOP. NU WH. Blow well
 & CO. RD. Rig released.