



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa FeLease No. 3F 078765Unit Rosa Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Rosa Unit

Farmington, New Mexico October 8, 1959

Well No. 35-51 is located 1835 ft. from S line and 1850 ft. from W line of sec. 5

NW/4 of Section 5

T-31-N

R-6-W

N.M.P.M.

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Undesignated Dakota

San Juan

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 6345 ft. (GL)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Total depth 8120' sand. Ran cement log and found top cement behind 7" casing set at 3914. Went in hole with Basch Ross 23 pound - 7" to 15 pound - 5" hanger with double lead seal rings with packoff and 492' 5" 15 pound liner, but unable to get below 350'. Pulled liner and hanger and found top lead seal damaged, repaired hanger and went in hole with liner and hanger. Unable to get below 4500'. Pulled liner and hanger and found one lead seal off and rubber pack off torn up. Ran Bowen casing scraper on drill pipe to 7650', pulled scraper, ran liner and hanger and was unable to get below 4675'. Ran 492' 5" 5 pound liner with Basch Ross plain 24 pound - 7" to 15 pound 5" liner hanger set 7628-8120. Cemented with 75 sacks neat alc set cement. After waiting on cement, tested top of 5" liner with 1000 psi, which held with no indication of pressure drop.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum CorporationAddress Box 487Farmington, New MexicoAttn: L. O. Speer, Jr.

ORIGINAL SIGNED BY

L. O. Speer, Jr.

By _____

Title Area Superintendent