MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

					_	
Parrie	٦,	4	12.	- 1.	-5	5

	ol UNDESIG	NATED	F	ormation	DAKO	TA	No.	_County_	SAN J	UAN
Ini	itial XX	Aı	nnual		Spec	ial		_Date of	Test	4-28 -62
	npany R & C									
Uni	it swi	Sec. <u>8</u>	_Twp3(N Rge	•• <u>13</u> W	V_Purc	haser 80	outhe rn U	nion	Gas Company
Cas	sing 444 V	vt. <u>11.6</u>	_I.D	Set	at 61	.75_Pe	rf. 59	8	To6	100
Tub	oing 24 V	Vt	_I.D	Set	at_ 60	75 Pe	rf. 607	75	ro6	095
Gas	Pay: From	596 8_To	6100	L	x	rG]	Bar.Pre	85
	ducing Thru:	-								
Dat	e of Complet	ion:		Packer	NON	Sin	gle-Brade Reservo	enhead-G. (G. or G	.O. Dual
	·					ED DATA		* -		
Tes	ted Through	(Prever)	(Choke)	(Neberi)				Type Tap:	5	
	· · · · · · · · · · · · · · · · · · ·	Flow	Data			Tubing	Data	Casing Da	ata	
No.	(Prover) (Line)	(Choke)	Press	Diff.			l			Duration of Flow
	(Line) Size	Size	psig	h _w	°F.	psig	°F.	psig	°F∙	Hr.
SI 1.		-750	- 			2022 360		2022 793		
2.						320		667		
<u>3.</u>		<u> </u>		-		288	80	622		3 Hours
5.				 						
				F	LOW CAL	CULATION	S			
	Coeffici	ent	P	ressure	Flow '	Temp.	Gravity	Compres	s.	Rate of Flow
No.	(24-Hon	r)	h. Da	nsia	Fact	tor	Factor F	Factor F _{DV}		Q-MCFPD 8 15.025 psia
		- / V			C 81		F _g	F _{pv}		3731
1. l				300					-	3/31
1. 2.	12.365									
1. 2. 3.	12,307									
1. 2. 3. 4. 5.	12,365									
3. 4. 5.	Liquid Hydro	d Hydroca		·	SSURE CA	ALCUIATIO	Speci Speci	fic Gravit		
3. 4. 5.	Liquid Hydro ity of Liqui	d Hydroca	rbons	·	cf/bbl. deg.	The second of th	Speci Speci	fic Gravit	P _C Cal	ing Fluid
3. 4. 5. 5. Sas 1. C. No.	Liquid Hydro ity of Liqui	d Hydroca	rbons(1-e-S)		cf/bbl. deg.	-Q) ² -e-s)	Speci Speci P _C	fic Gravit	y Flow	ing Fluid
3. 4. 5. 5. No.	Liquid Hydro ity of Liqui	d Hydroca	rbons(1-e-S)		cf/bbl. deg.	-Q) ² -e-s)	Speci Speci P _C	fic Gravit	P _C Cal	ing Fluid
3. 4. 5. 5. No.	Liquid Hydro ity of Liqui	d Hydroca	rbons(1-e-S)		cf/bbl. deg.	-Q) ² -e-s)	Speci Speci P _C	fic Gravit	P _C Cal	ing Fluid
3. 4. 5. No. 1. 2. 3. 4. 5.	Liquid Hydro ity of Liqui P _w Pt (psia)	d Hydroca	rbons(1-e-s)_		cf/bbl. deg.	-Q) ² -e-s)	Speci Speci P _C	fic Gravit	P _C Cal	ing Fluid
3. 4. 5. No. 1. 2. 3. 4. 5. Absorption	Liquid Hydro ity of Liqui Pw Pt (psia) plute Potent	Pt lial:3	F _c Q	(F _c Q) ²	Cf/bbl. deg. (F, (1-	n75	Speci Speci Pc- Pw2	fic Gravit	P _C Cal	ing Fluid
Absorption ADDR	Liquid Hydro ity of Liqui Pw Pt (psia)	Pt ial:	F _C Q 950 DRILLIN	(F _c Q) ²	(F, (1-	n75	Speci Speci P _c P _w 2	P _c -P _w ²	y Flow	ing Fluid
Absorption Additional Commerce of the Additional	Liquid Hydro ity of Liqui Pw Pt (psia) Plute Potent PANY RESS WT and TITLE	Pt ial:	F _C Q 950 DRILLIN	(F _c Q) ²	(F, (1-	n75	Speci Speci P _c P _w 2	fic Gravit	y Flow	I. P. Pc
Absorption Additional Commerce of the Additional	Liquid Hydro ity of Liqui Pw Pt (psia) Plute Potent PANY RESS WT and TITLE	Pt ial:	F _C Q 950 DRILLIN	(F _c Q) ²	cf/bbl. deg. (F. (1-	n75	Speci Speci P _c P _w 2	P _c -P _w ²	PC Cal	Pw Pc
Absorption Additional Commerce of the Additional	Liquid Hydro ity of Liqui Pw Pt (psia) Plute Potent PANY RESS WT and TITLE	Pt ial:	F _C Q 950 DRILLIN	(F _c Q) ²	(F, (1-	n75	Speci Speci P _c P _w 2	P _c -P _w ²	PC Cal	I. P. Pc

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- F_{g} : Gravity correction factor.
- F_t Flowing temperature correction factor.
- $\mathbf{F}_{\mathbf{DV}}$ Supercompressability factor.
- n _ Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.