

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office New MexicoLease No. 03566Unit Stewart

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Water Fracture</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 23, 1956

Well No. 5 is located 1650 ft. from N line and 990 ft. from W line of sec. 20S Section 20
(¼ Sec. and Sec. No.)30N
(Twp.)10W
(Range)DM
(Meridian)Blanco
(Field)San Juan
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6221 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, including points, and all other important proposed work)

April 13, 1956 Total Depth 5200', Clearance depth 5100'. Water fractured Point Look-out perf. intervals 4947-4956, 5011-5019, 5042-5052 & 5064-5074 (4 holes/ft.) with 100,800 gals. water & 100,000# sand. BDP 1600#, Max. Pr. 2200#, Avg. Tr. Pr. 1800#. Injection rate 45.5 bbls./min. Flush 5200 gallons.

April 13, 1956 T.D. 5200', Temp. Bridge Plug @ 4910'. Water fractured Lower Manoshee perf. intervals 4788-4795, 4840-4847 & 4861-4867 (4 holes/ft.) with 69,800 gallons water & 60,000# sand. BDP 2250#, max. pr. 2400#, avg. treating pr. 2250#. Injection rate 44.5 bbls./min. Flush 5200 gallons.

April 14, 1956 T.D. 5200', Temp. bridge plug @ 4770'. Water fractured Middle Manoshee perf. intervals 4686-4698 & 4713-4722 (4 holes/ft.) with 70,700 gallons water & 60,000# sand. BDP 1800#, max. pr. 2100#, Avg. tr. pr. 1950#. Injection rate 41.7 bbls./min. Flush 5200 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas CompanyAddress Box 997Farmington, New MexicoBy [Signature]
Title Petroleum Engineer