

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(Insert instructions on reverse side)

3. LEASE DESIGNATION AND WELL NO.

14-20-0603-539

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

King Kong

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

Salt Creek Dakota

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec. 4, T30N, R17W

12. COUNTY OR PARISH; 13. STATE

San Juan

New Mex.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TASCO

3. ADDRESS OF OPERATOR

501 Airport Dr. Suite 110, Farmington, N.Mex.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

2170 FNL 2460 FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged: Cement from 1065 to 915 with 10 sacks of Cement.

Cement from 515 to 415 with 20 sacks of cement

Cleaned and graded location

Placed dry hole marker and 10 sack cement plug in top of well



18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Operator

DATE May 16, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY.

HYMOCC

*See Instructions on Reverse Side