Form 9-331 (May 1963)

16.

UNITED STATES DEPA

SUBMIT IN TRIPLICATE*

Form approved, Budget Bureau No. 42 R1424. 5. LEASE DESIGNATION AND SERIAL NO.

ARTMENT	OF	THE	INTERIOR	verse side)	on

SF077231 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to Use "APPLICATION FOR PERMIT--" for such proposal different reservoir. 7. UNIT AGREEMENT NAME WELL WELL X OTHER 8. FARM OR LEASE NAME 2. NAME OF OPERATOR Shaw El Paso Natural Gas Company 9. WELL NO. 3. ADDRESS OF OPERATOR 1-A P. O. Box 990, Farmington, MM LOCATION OF WELL (Report location clearly and in accordance with any State See also space 17 below.) At surface 10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T-30-N, R-9-W 955'N, 1190'W N.M.P.M. 12. COUNTY OR PARISH | 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. San Juan New Mexico 5871' GL

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
				[V]		
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT X	ALTERING CASING	
RHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL		CHANGE PLANS		(Other) Report results of mu	Itiple completion on Well	
(Other)				(Note: Report results of mu Completion or Recompletion I	Report and Log form.)	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - TD 2916'. Ran 71 joints 7", 20#, K-55 intermediate casing, 2904' set at 02-25-75 2916'. Cemented with 329 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 275'.
 - TD 5209'. Ran 75 joints 4 1/2", 10.5#, J-55 casing liner, 2453' set from 03-01-75 2756' to 5209'. Float collar set at 5175'. Cemented with 426 cu. ft. cement. WOC 18 hours.
 - PBTD 5180'. Perf'd Point Lookout 4861', 4872', 4882', 4892', 4905', 4929', 4951', 4975', 4993', 5007', 5024', 5044', 5058', 5083', 5114', 5130', 5159' 03-24-75 with 1 shot per zone. Frac'd with 12,000# 100 mesh sand and 100,000#--20/40 sand and 128,000 gallons water. No ball drops. Flushed with 6000 gallons

Perf'd Cliff House 4296', 4389', 4406', 4433', 4458', and 4473' with 1 shot per zone. Frac'd with 50,000#--20/40 sand and 55,932 gallons water. No ball drops. Flushed with 5880 gallons water.

18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling	Clerk DATE March 27, 1975
(This space for Federal or State office use) APPROVED BY	APR 1 1975
*See Instructions on Revers	e Side U. S. GEDI COION SURVEY