

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
SLM

94 FEB 23 AM 11:33

Sundry Notices and Reports on Wells

RECEIVED

FEB 28 1994

OIL CON. DIV.

DIST. 3

070 FARMINGTON, NM

1. Type of Well
GAS

5. Lease Number
SF-077231

6. If Indian, All. or
Tribe Name

2. Name of Operator
MERIDIAN OIL

7. Unit Agreement Name

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
Shaw #1A

9. API Well No.

4. Location of Well, Footage, Sec., T, R, M

955' FNL, 1190' FWL Sec. 13, T-30-N, R-9-W, NMPM

10. Field and Pool
Blanco PC & MV

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injectio

☒ Other - pay add

13. Describe Proposed or Completed Operations

02-06-94 MOL&RU. ND WH. NU BOP. TOOH w/1 1/4" tbg. TOOH w/2 3/8" tbg.

02-07-94 TIH, sting into pkr @ 2730' and TOOH. Ran scraper to 5180'. Set RBP @ 4270'. Load hole w/wtr. Run CBL/CCL/GR f/4270'.

02-08-94 TOOH w/RBP. TIH, set RBP @ 4833'. Dump sand. Load hole w/KCI wtr. Set FBP @ 4790'. PT RBP 3800#/15 min, ok. Spot 200 gal acid. Perf Menefee 4532-4816' w/2 spf, 50 holes. Set FBP @ 4500'. BD w/1200 gal acid. Est rate. Set pkr @ 4500'. SI for pressure build up.

02-09-94 SI for pressure build up. Pull pressure bomb.

02-10-94 Frac Menefee w/40,070# 40/70 sand and 20,740# 20/40 sand and 83,496 gal. x-link gel. TOOH w/pkr. Set RBP @ 4270'. Set FBP @ 4150'. PT RPB @ 3800 psi. Spot 500 gal acid across Lewis. TOOH w/pkr. Perf Lewis 3420-4165' w/2 spf. Set FBP @ 3343'. Spot 1500 gal acid. Pull up to 3343' and reset pkr. Frac Lewis w/167,480# 20/40 sand and 118,323 gal gel wtr. TOOH w/pkr.

02-11-16 Blow well and CO.

02-17-94 Set pkr @ 2740'. Ran 76 jts 2 3/8", 4.7#, J-55 8rd EUE tbg, locator seal assembly and 86 jts 2 3/8", 4.7#, J-55 8rd EUE tbg landed @ 5133'. Seating nipple @ 5100'. Ran 82 jts 1 1/4", 2.4#, J-55 10rd NU tbg landed @ 2693'. Seating nipple @ 2660'. ND BOP. NU WH. Released rig.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 2/20/94

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

FEB 24 1994

FARMINGTON DISTRICT OFFICE

BY [Signature]

NMOCD