NO. OF COPI	ES RECEIVED 4				Form C		
DISTRI	NOITUE	_			Superse C•102 a	aes Ola nd C-103 ,	
SANTA FE	/	NEW ME	EXICO OIL CONS	ERVATION COMMISSION	Effective	e 1-1-65	
FILE		1			Feet to decree	T	
U.S.G.S.		_			State State	Type of Lease	
LAND OFF	ICE					& Gas Lease No.	
OPERATOR	7	_			E-1193		
	· · · · · · · · · · · · · · · · · · ·				kmm		
	SUNDI OT USE THIS FORM FOR PR USE "APPLICA	RY NOTICES AND ROPOSALS TO DRILL OR T	REPORTS ON OF PLUG I ORM C-101) FOR SUC	WELLS BACK TO A DIFFERENT RESERVOIR H PROPOSALS.	4/////	eement Name	
OIL WELL	GAS WELL X	OTHER-		1111 35 176	}		
2. Name of Op	erator			4 - × 0 19:10	EPNG (Lease Name	
El Paso	Natural Gas Con	mpany		A COM.	9. Well No.		
3. Address of	-		_	CHST. 3	5A		
P. O. Box 990, Farmington, NM 87401						10. Field and Pool, or Wildcat	
4. Location of				1000	Dianas	Mesa Verde	
UNIT LET	TER	800 FEET FROM	M THEN	LINE AND	FEET FROM		
THE	W LINE, SECT	710N36	TOWNSHIP30N	RANGE 8W	нмрм.		
mm	mmm	15 Eleva	tion (Show whether	DF, RT, GR, etc.)	12. County		
			6040' GL		San Jı	uan ((((((()	
16.	<u> </u>	Assessing Por		Nature of Nation Paper			
		INTENTION TO:	. To indicate i	Nature of Notice, Report	EQUENT REPORT	OF:	
	<u></u>		S AND ABANDON	REMEDIAL WORK		ALTERING CASING	
PERFORM REM	一	PLU	S AND ABANDON	COMMENCE DRILLING OPHS.	Ħ	PLUG AND ABANDONMENT	
TEMPORARILY	7	CHAI	NGE PLANS	CASING TEST AND CEMENT JOE	 		
PULL OR ALTE	R CASING	Ç NA		OTHER Perf and	Frac		
OTHER							
• • • • • • • • • • • • • • • • • • • •					·		
	Proposed or Completed (ERULE 1703.	Operations (Clearly sta	ite all pertinent de	tails, and give pertinent dates,	including estimated do	ite of starting any proposea	
20.0, 02							
04-01- 76	O4-01-76 TD 3100'. Ran 75 joints 7", 23#, N-80 intermediate casing, 3088' set at 3100'. Cemented with 927 cu. ft. cement. Still had bradenhead flow. Squeezed bradenhead with 377 cu. ft. cement. WOC 12 hours.						
04-0 6-76	Due to collapsed pipe at 275', a 50 sk. cement plug was set at 328'.						
04-11- 76	TD 5476'. Ran 171 joints 4 1/2", 10.5#, KS production casing, 5464' set at 5476'. Float collar set at 5459'. Cemented with 431 cu. ft. cement. WOC 18 hours. Top of cement at 2400'.						
07-20-7 6	7-20-76 PBTD 5459'. Tested casing to 3500#, held OK. Perf'd 4557', 4626', 4634', 4642', 4658', 4683', 4698', 4714', 4770', 4880', 4890', 4900', 4965' with 1 shot per zone. Frac'd with 82,000#20/40 sand and 82,160 gallons water. No ball drops. Flushed with 3350 gallons water.						
Perf'd 5075', 5084', 5094', 5104', 5114', 5124', 5134', 5151', 5165', 5190', 52 5234', 5279', 5300', 5328', 5348', 5375' with 1 shot per zone. Frac'd with 90, 20/40 sand and 90,000 gallons water. No ball drops. Flushed with 3730 gallons						d with 90,000#	
18. I hereby sertify that the information above is true and complete to the best of my knowledge and belief.							
(,	And The	adfield	TITLE	Drilling Clerk	DATE	July 21, 1976	
SIGNED	***		11166				
Original	Signed by A. R	. Kendrick	TITLE	smeriks bur. 🚜	DATE_	JUL 25 13/6	

CONDITIONS OF APPROVAL, IF ANY: