

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

NM-28760

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Little Federal

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT  
Undesignated Pictured

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA  
Cliffs

Sec. 12-T30N-R14W

N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mex.

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

ODESSA NATURAL CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 3903, Odessa, Texas 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

940'FNL, 790'FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5899'GR, 5909'DF, 5910'KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-23-77. Spud well. T. D. 101'.

Ran 2 jts, 8-5/8", 28.0 lb, 8-V casing (83.00') set at 91.00' with 100 sacks Class "B" cement with 2% CaCl & 1/4 lb. Flocele per sack. Cement circulated. Test O.K. with 500 psig.

3-26-77. T. D. 1850'.

Ran 46 jts, 4-1/2", 10.50 lb. CW-55 casing (1792.44') set at 1803.44' with 175 sxs. 65/35 Pozmix (12% gel) followed by 250 sacks 50-50 Pozmix with 6-1/4 lbs. Gilsonite per sack. Cement circulated.

APR 14 1977

For: Odessa Natural Corporation

18. I hereby certify that the foregoing is true and correct

SIGNED Ewell N. Walsh, P. E.

President, Walsh Engineering  
& Production Corp.

TITLE

DATE 4/13/77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side