Form 9-331 (May 1953)

UNITED STATES SUBMIT IN TRIPLICATE* Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERVE NO.

GEOLOGICAL	SURVEY
-------------------	--------

GEOLOGICAL SURVEY			SF-078138A		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)		6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
1. OIL GAS X			7. UNIT AGREEMENT NA	TME	
WELL WELL OTHER 2. NAME OF OPERATOR			8. FARM OR LEASE NAME		
Aztec Oil & Gas Company			Current		
3. ADDRESS OF OPERATOR		9. WELL NO.			
P. O. Drawer 570, Farmington, New Mexico		# 2			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT Basin Dakota			
1750' FNL & 1450' FEL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
		Section 11-30N-11W			
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)		DF, RT, GR, etc.)	12. COUNTY OR PARISE	13. STATE	
	5922'	GR	San Juan	New Mexico	
16. Check Ap	propriate Box To Indicate	Nature of Notice, Report, or C	Other Data		
NOTICE OF INTENTION TO:		UENT REPORT OF:	,		
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	OULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	(Note: Report results Completion or Recomp	REPAIRING ALTERING C ABANDONME and Casing r s of multiple completion letion Report and Log fo	easing ent* eportX on Well orm.)	
17. DESCRIBE PROPOSED OR COMPLETED OPE proposed work. If well is direction nent to this work.)*	RATIONS (Clearly state all pertine mally drilled, give subsurface loc	ent details, and give pertinent dates, cations and measured and true vertic	, including estimated da al depths for all marker	te of starting any es and zones perti-	

Spudded 12-1/4" surface hole at 5:30 AM 9-4-77. 9 - 4 - 77

Ran 5 jts of 9-5/8", 36#, K-55, set at 216.96'. Cemented with 125 sacks Class B with 1/4# gel flake per sack and 3% CaCl. Cement circulated to surface.

Plug down at 1:15 PM 9-4-77.

SEP 12 19/7

