

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 790' FSL - 1850' FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) _____

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

(NOTE: Report results of multiple completion or zone changes on Form 9-330.)

AUG 09 1982

U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged and abandoned well as follows:

1. Filled 2-7/8" O.D., 6.4#, J-55, 10R, tubing for casing, squeezing *from 1520' to surface*
Farmington Fruitland Formation perfs ~~to surface~~ using 30 sx cement. Braden-head squeezed bottom and top of Ojo Alamo in annulus ~~and casing~~ with 7 sx class "B" neat cement on 7-30-82.
2. Installed permanent dry hole monument.
3. Filled all pits.
4. Cleaned well location of all equipment, pipe, junk, and trash.
5. Cut off tie-downs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sherman E. Dugan TITLE Agent DATE 8-6-82

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

RECEIVED
JAN 24 1985

*See Instructions on Reverse Side
OIL CON. DIV.
DIST 3

APPROVED
AS AMENDED

JAN 21 1985

W. J. Stan McKee
for M. MILLENBACH
AREA MANAGER

NMOCC