

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1570' FNL x 1055' FEL, Section 9,
AT SURFACE: T-30-N, R-9-W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO: | SUBSEQUENT REPORT OF: |
|---|--------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* <input type="checkbox"/> | <input type="checkbox"/> |
| (other) <u>Spud & Set Casing</u> | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- Spudded 13-1/4" hole on 3/18/78. Drilled to 288'. Set 9-5/8" 32.3#, H-40 casing with 300 sx Class "B", 2% CaCl₂. Circulated 10 bbls. good cement. Pressure tested to 600#; held OK.

Rig fire at Arapahoe Rig #1. Well name changed to Elliott Gas Com "W" No. 1. Well completed as Pictured Cliffs.

Rolled out 9-5/8" casing.

Drilled 8-3/4" hole to 2948'. Set 7" 20#, K-55 protective casing at 273' with 100 sx Class "B", 2% CaCl₂. Circulated 20 sx. Drilled 6-1/4" hole to a total depth of 3125'. Set 4-1/2" 10.5#, K-55 casing at 3125' with 1050 sx Class "B", 50:50 Poz, 6% gel. Circulated 200 sx good cement. 2 lbs. medium Tuf Plug per sx. Tailed in with 100 sx Class "B" Neat. Rig released 4/9/78. Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SYCORA TITLE Area Adm. Supvr. DATE 5/5/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

5. LEASE

SF 073139

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Elliott Gas Com "W"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SE/4 NE/4 Section 9,
T-30-N, R-9-W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. API NO.

30-045-22931

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6193' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

MAY 8 1978