

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

5. LEASE SF 080776
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Florance F.
9. WELL NO. 1A
10. FIELD OR WILDCAT NAME Blanco M.V.
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Sec. 25; T-30-N, R-10-W N.M.P.M.
12. COUNTY OR PARISH San Juan
13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 5990' GL

1. oil well ☐ gas well ☒ other
2. NAME OF OPERATOR El Paso Natural Gas Company
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1510'S, 1560'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☒
FRACTURE TREAT	☐	☒
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other)	☐	☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-14-79: TD 2926'. Ran 72 jts. 7", 20#, KS intermediate casing, 2910' set at 2926'. Cemented w/361 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1500'.

3-17-79: TD 5304'. Ran 80 jts. 4 1/2", 10.5#, KS casing liner, 2559' set 2745-5304'. Float collar set at 5271'. Cemented w/445 cu. ft. cement. WOC 18 hours.

4-06-79: PBTD 5271'. Tested casing to 3500#, OK. Perfed Lower P.L. 4994, 5006, 5068, 5133, 5176, 5191, 5201' w/1 SPZ. Fraced w/29,000# 20/40 sand and 40,000 gal. water. Flushed w/6300 gal. water. Perfed Lower Men. & Mass. P.L. 4658, 4689, 4716, 4767, 4775, 4811, 4818, 4831, 4837, 4843, 4849, 4855, 4877, 4883, 4889, 4895, 4901, 4907, 4913, 4919, 4925, 4931, 4953, 4959' w/1 SPZ. Fraced w/78,000# 20/40 sand and 156,000 gal. water. Flushed w/6174 gal. water.

(OVER)


Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Busco TITLE Drilling Clerk DATE April 9, 1979

(This space for Federal or State office use)
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NYMOCC



There is a discrepancy in the number of items reported in the two reports.
(The number of items in the two reports is 10 and 12 respectively.)

REQUEST FOR APPROVAL FOR	☐
BEST WATER AVAILABLE	☐
BRACKETED AREA	☐
PHOTO OF AREA	☐
REPAIRS WILL	☐
PULL OR AFTER CARING	☐
ADDITIONAL COMMENTS	☐
CHANGES ZONES	☐
REMARKS	☐
(Initial)	☐

Figure 1

157. DEDUCTIBLE FOR OR COMPLETED OPERATIONS (OTHERWISE STATED BY REFERENCE TO THIS FORM) IN THE YEAR FOR WHICH THE RETURN IS MADE:

4-10-74
4-11-74
4-12-74
4-13-74
4-14-74
4-15-74
4-16-74
4-17-74
4-18-74
4-19-74
4-20-74
4-21-74
4-22-74
4-23-74
4-24-74
4-25-74
4-26-74
4-27-74
4-28-74
4-29-74
4-30-74
5-1-74
5-2-74
5-3-74
5-4-74
5-5-74
5-6-74
5-7-74
5-8-74
5-9-74
5-10-74
5-11-74
5-12-74
5-13-74
5-14-74
5-15-74
5-16-74
5-17-74
5-18-74
5-19-74
5-20-74
5-21-74
5-22-74
5-23-74
5-24-74
5-25-74
5-26-74
5-27-74
5-28-74
5-29-74
5-30-74
5-31-74
6-1-74
6-2-74
6-3-74
6-4-74
6-5-74
6-6-74
6-7-74
6-8-74
6-9-74
6-10-74
6-11-74
6-12-74
6-13-74
6-14-74
6-15-74
6-16-74
6-17-74
6-18-74
6-19-74
6-20-74
6-21-74
6-22-74
6-23-74
6-24-74
6-25-74
6-26-74
6-27-74
6-28-74
6-29-74
6-30-74
7-1-74
7-2-74
7-3-74
7-4-74
7-5-74
7-6-74
7-7-74
7-8-74
7-9-74
7-10-74
7-11-74
7-12-74
7-13-74
7-14-74
7-15-74
7-16-74
7-17-74
7-18-74
7-19-74
7-20-74
7-21-74
7-22-74
7-23-74
7-24-74
7-25-74
7-26-74
7-27-74
7-28-74
7-29-74
7-30-74
7-31-74
8-1-74
8-2-74
8-3-74
8-4-74
8-5-74
8-6-74
8-7-74
8-8-74
8-9-74
8-10-74
8-11-74
8-12-74
8-13-74
8-14-74
8-15-74
8-16-74
8-17-74
8-18-74
8-19-74
8-20-74
8-21-74
8-22-74
8-23-74
8-24-74
8-25-74
8-26-74
8-27-74
8-28-74
8-29-74
8-30-74
8-31-74
9-1-74
9-2-74
9-3-74
9-4-74
9-5-74
9-6-74
9-7-74
9-8-74
9-9-74
9-10-74
9-11-74
9-12-74
9-13-74
9-14-74
9-15-74
9-16-74
9-17-74
9-18-74
9-19-74
9-20-74
9-21-74
9-22-74
9-23-74
9-24-74
9-25-74
9-26-74
9-27-74
9-28-74
9-29-74
9-30-74
10-1-74
10-2-74
10-3-74
10-4-74
10-5-74
10-6-74
10-7-74
10-8-74
10-9-74
10-10-74
10-11-74
10-12-74
10-13-74
10-14-74
10-15-74
10-16-74
10-17-74
10-18-74
10-19-74
10-20-74
10-21-74
10-22-74
10-23-74
10-24-74
10-25-74
10-26-74
10-27-74
10-28-74
10-29-74
10-30-74
10-31-74
11-1-74
11-2-74
11-3-74
11-4-74
11-5-74
11-6-74
11-7-74
11-8-74
11-9-74
11-10-74
11-11-74
11-12-74
11-13-74
11-14-74
11-15-74
11-16-74
11-17-74
11-18-74
11-19-74
11-20-74
11-21-74
11-22-74
11-23-74
11-24-74
11-25-74
11-26-74
11-27-74
11-28-74
11-29-74
11-30-74
12-1-74
12-2-74
12-3-74
12-4-74
12-5-74
12-6-74
12-7-74
12-8-74
12-9-74
12-10-74
12-11-74
12-12-74
12-13-74
12-14-74
12-15-74
12-16-74
12-17-74
12-18-74
12-19-74
12-20-74
12-21-74
12-22-74
12-23-74
12-24-74
12-25-74
12-26-74
12-27-74
12-28-74
12-29-74
12-30-74
12-31-74

-----sayT ons uachA leviS yofeS eashuSduS
toemS bns eunI zI gnoyeyol eSrtayT yInes ydeveS I .zI

TRAC MR. J. G. MILLER DATE 8-2-54 PAGE ONE

Fraced w/95,500# 20/40 sand and 191,000 gal. water.
Flushed w/5880 gal. water.

Perfed C.H. & Upper Men. 4154,4201,4208,4215,4236,4243,
4250,4257,4264,4271,4294,4302,4324,4331,4338,4345,4352,
4471,4487,4527,4536,4550,4557,4564,4571,4586' w/1 SPZ. 5745

*See instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

s of such operations when completed, as indicated, on Federal and
on all lands in such State, pursuant to applicable State law and
be submitted, particularly with regard to local, area, or regional
Federal and/or State office.
described in accordance with Federal requirements. Consult local
cial information as is required by local Federal and/or State offices
or present productive zones, or other zones with present significant
cement plugs; mud or other material placed below, between and
ny left in the hole; method of closing top of well; and date well site