5. LEASE

SF 078438

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790'S, 1780'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SHOOT OR ACIDIZE REPAIR WELL SHOOT OR ACIDIZE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* -5-79: TD 3875'. Ran 94 joints 7", 20#, KS intermediate casing, 3863' set at 3875' Cemented w/466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 3350'. -8-79: TD 6251'. Ran 79 joints. 4½", 10.5#, K-55 casing liner, 2586' set at 3594-6180'. Float collar set at 6173'. Cemented w/445 cu. ft. cement. WOC 18 h	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1. oil well well other 2. NAME OF OPERATOR E1 Paso Natural Gas Company 3. ADDRESS OF OPERATOR BOX 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790'S, 1780'E AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally direct, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally direct, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally direct, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally direct, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 18. Leevations (RION WILLIAM PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is dincluding estimated date of starting any proposed work. If well is		San Juan 32-9 Unit
El Paso Natural Gas Company 3. ADRESS OF OPERATOR BOX 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SUPFACE: 790'S, 1780'E AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OF ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 18. Thereby depths that the foregoing is true and correct SIGNED SUBSURFACE DATE 19. FIELD OR WILDCAT NAME Blanco MV 11. SEC.T.R. M., OR BLK. AND SURVEY. AREA Sec. 8, T-31-N, R-9-W N.M.P.M. 12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. 16. CHECK APPROPALE 12. STATE SAN JUAN NEW MEXICO 17. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. 18. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. 19. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. 10. FIELD OR WILDCAT NAME Blanco MV AREA Sec. 8, T-31-N, R-9-W N.M.P.M. 12. COUNTY OR PARISH 13. STATE San Juan New Mexico 16. CHECK APPROPHATE SAN JUAN NEW MEXICO 17. API NO. 18. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. 19. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. 10. FIELD OR WILDCAT NAME SHOW APPORT NAME APP	=: -:: } 0	San Juan32-9 Unit
Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790'S, 1780'E AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 18. 10 G 251'. Ran 94 joints 7", 20#, KS intermediate casing, 3863' set at 3875'. Cemented W/466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 3350'. 18. 79: TD 6251'. Ran 79 joints. 4½", 10.5#, K-55 casing liner, 2586' set at 3594-6180'. Float collar set at 6173'. Cemented W/445 cu. ft. cement. WOC 18 h Subsurface Safety Valve: Manu. and Type 18. I hereby deriffy that the tyregoing is true and correct SIGNED MANUALLAL TITLE DITILLING CLERK DATE August 10, 1979		
AT SURFACE: 790'S, 1780'E AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP ADDRESS: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP ADDRESS: AT TOP PROD. INTERVAL: AT TOP ADDRESS: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP ADDRESS: AT TOP PROD. INTERVAL: AND INTERVAL: A PI NO. 15. ELEVATIONS (SHOW DF, KDB, AND W 6686' G.L. (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Report results of multiple completion or zo change on Form 9-330.) (NOTE: Seport results of multiple c	Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY O
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: San Juan New Mexico 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE Change on Form 9-330.) WILLIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 15. TO 3875'. Ran 94 joints 7", 20#, KS intermediate casing, 3863' set at 3875' Cemented w/466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 3350'. 18. To 6251'. Ran 79 joints. 4½", 10.5#, K-55 casing liner, 2586' set at 3594-6180'. Float collar set at 6173'. Cemented w/445 cu. ft. cement. WOC 18 h AUG 10 F. Subsurface Safety Valve: Manu. and Type U. Second Collaboration of the completion of the completion of the completion of the collar set at 6173'. Cemented w/445 cu. ft. cement. WOC 18 h AUG 10 F. Subsurface Safety Valve: Manu. and Type U. Second Collaboration of the completion	below.)	N.M.P.M.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	AT TOP PROD. INTERVAL:	San Juan New Mexico
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dat including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* 5-79: TD 3875'. Ran 94 joints 7", 20#, KS intermediate casing, 3863' set at 3875'. Cemented w/466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 3350'. 8-79: TD 6251'. Ran 79 joints. 4½", 10.5#, K-55 casing liner, 2586' set at 3594-6180'. Float collar set at 6173'. Cemented w/445 cu. ft. cement. WOC 18 h LUG 10 ** LUG 10 ** LUG 10 ** Subsurface Safety Valve: Manu. and Type U. s. GEOLOGICA LUG 10 ** LU	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD
Including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* -5-79: TD 3875'. Ran 94 joints 7", 20#, KS intermediate casing, 3863' set at 3875' Cemented w/466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 3350'. -8-79: TD 6251'. Ran 79 joints. 4½", 10.5#, K-55 casing liner, 2586' set at 3594-6180'. Float collar set at 6173'. Cemented w/445 cu. ft. cement. WOC 18 h LUC 10 Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct signed from the foregoi	FRACTURE TREAT	(NOTE: Report results of multiple completion or zon change on Form 9–330.)
Cemented w/466 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 3350'. 8-79: TD 6251'. Ran 79 joints. 4½", 10.5#, K-55 casing liner, 2586' set at 3594-6180'. Float collar set at 6173'. Cemented w/445 cu. ft. cement. WOC 18 h Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct signed Many Juntual Title Drilling Clerk DATE August 10, 1979	including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent-5-79: TD 3875'. Ran 94 joints 7", 20#, KS intermedi	rectionally drilled, give subsurface locations and to this work.)* ate casing, 3863' set at 3875'
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Many Manual TITLE Drilling Clerk DATE August 10, 1979	Cemented w/466 cu. ft. cement. WOC 12 hours,h	eld 1200#/30 minutes. Top of
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Japan Season TITLE Drilling Clerk DATE August 10, 1979		/445 cu. ft. cement. WOC 18 ho
SIGNED SEARCH TITLE Drilling Clerk DATE August 10, 1979	Subsurface Safety Valve: Manu. and Type	U. S. GEOLOGICAL FI
		k para August 10 1070
		· · · · · · · · · · · · · · · · · · ·
APPROVED BY TITLE DATE		\