NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

-			NOH	KTHWEST N	IEW MEX.	ICO PAGA	JDT. →LLS	ALAGE	1501	V	Cell		
Operator	ator Tenneco Oil C				Company Lea			Flor	rance	l	lo	114/	
Location						<i>T</i> 7		_	Cour	·+ · · · · · ·		,	
of Well:	Unit_	<u>L_Sec1</u>	<u>] </u>	30	Time	Rge of Prode	·	et.hod	Cour	ncy <u>Sa</u> Pro	n Jua od Me	n. ed i iiii	
	Nam	e of Reser	zoir d	or Pool	(Oil	or Gas)	(F1	ow or	Art. Lift)	(Tb	g. or	Ceg.)	
Upper	1,4411									l		5 A.	
	ompletion Pictured			Cliff		Gas		Flow		Tubir		10	
Lower		Dania (\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		GAs			Flow	نو		Tubin	na	
Completio	n	Basin [dKOLd	PRE_F		T-IN PRE					10511	- The second second	
Upper Hou	r date	1/18/83	T	Length o	$\circ f$		15	SI pres	S.	Stal	oiliz	edy	
	Compl Shut-in 10:00 a.			. time shut-in /2 110			ors bsig 335			(Ye	(Yes or No) No		
Lower Hour, date 4/18/83 Compl Shut-in 10:00 a.			_	Length of			~c	I pres	:s. 1084	084 (Yes or No) ho			
Cormenced	at (bo	our, date)*	4/2	21/83	1 · 30 n	. m .	2	Zone pr	oducing (U	pper or	Lowe	T) II IIII ON	
Time	La	psed time		Pres	sure		rod.	. Lone				13(1-1-	
(hour, da	ite)	since*	Upper	Compl.	Lower	Compl.	Tem	0.		Remarks			
4/22/83			342	,	182	2							
10:00 a 4/23/83		21 hours	J+2		101		i					- Par	
12:00 n	oon	47 hours	352	2 _	11!	5							
							 						
												- no little de deserta	
	i-											-	
							 						
Production	on rate	during tes	t							-		100	
Oil:		30PD ba	o hee	n	Bt	ols.in_		Hr:	S. meter	Grav	. 1	CA	
Gas:	-0-	<u>1</u>	CFPD;	100004	O111 (4 ()	/1 · · ·		, , , , , , , ,		(_logg:	<u>ed 0+</u> :		
Upper Hour, date				MID-TEST SHUT-IN PR			1	SI pre	SS.	,	biliz		
Compl Shut-in				time shut-in			osig				(Yes or No) Stabilized?		
Lower Hour, date			1	Length of time shut-in			SI prass. psig			(Yes or No)			
Compl	Shut-in			time shu	FLO	V TEST N	0. 2						
Sommerice	d at (h	our, date)	⊹⊁				- 1		roducing (U	Joper Or	Lowe	er);	
	1.7	+	1	Pres	sure		Prod	. Zone		Remarks	:		
(hour, d	ste)	since **	Upper	· Compl.	Lower	Compl.	1 16	• СШ	<u> </u>	Hower V	· · · · · · · · · · · · · · · · · · ·		
					1								
									 -				
							i		1				
			 		 		,						
							<u>i</u>						
	T						!			•			
			 		 		•		1 1	i. Š	₩,		
1									ل الله	4. J			
Froincti	on rate	during te	st					1.5					
Cil:		30PD b	ased :	on	3 4 + 2 mi	ols. in Comifica	- or	.ars (ster):	Gr	= Y •		* · · · · · · · · · · · · · · · · · · ·	
Gas:			_MUSS.	ມ; 1₹5te	a onra	(Oz 32 200	. J			·			
ferarks:	:												
	·	10											
-		and the second s		an ina managa da an ang ang ang ang ang ang ang ang ang	Same to	سعاد المادية المستوالية. والمحارف في المرادية إلا إلى الم	· i	irus a	and samplet	e to th	ල රිගුම	6 18 44	
		ry that the	AFALC Research	2224629.1 4	المشت الله مدر								
સાજસૌદદૈકૃ	_	i gayatka		eg .		ည့်နောင်း	سستوني		ifeer_Gil.S	<u>יעמינטטי</u>			
Nggasia	· · · · · · · · · · · · · · · · · · ·	T BEE ENVS		29		- 1 P	411			선물 목동	urina	January	
Man Mo	vice (ii	i dini past	ina 1	in hideli	a,	,						. 14. 1 [8]	
a .	Origin	al Signed by CH	ARLES G	HOLSON .		Title			erit			manager de l'ang	
<i>₹</i> ./													
11:13	DEPU	li vii see g	ال المالية	G. Aller He		7113,			ng Nam 23,,				

- 1. A packer leakage test shall be consenced on each sultiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the sultiple completion. Such tests shall also be consenced on all sultiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- 2. At least 72 hours prior to the commencement of any packer leaking the the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall slso be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shutin accordance with Paragraph 3 above.
- 5. Flow Test Ro. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gar-zone tests must be measured on each zone with a deaderight prossure gauge at time intervals as follows: 3-hour tests: ixaediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells, which have previously shown questionable test data.
- 24-bour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas some.
 - 8. The results of the above—described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Nexico-Oil Conservation Commission on Morthwest New Nexico Packer Leakage Test Fpra Revised 11-1-58, with all deadeeight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).— A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon.—For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form.

