

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Blackwood & Nichols Co., Ltd.

3. ADDRESS OF OPERATOR
P.O. Box 1237, Durango, Colo. 81301

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' F/NL - 1490' F/EL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
NM 03358

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
NEBU Agrmt. No. 1, Sec. 929

8. FARM OR LEASE NAME
Northeast Blanco Unit

9. WELL NO.
203

10. FIELD OR WILDCAT NAME
South Los Pinos-Fruitland - PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
C-11-31N-7W

12. COUNTY OR PARISH | 13. STATE
San Juan | New Mexico

14. API NO.
30-045-23485

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6546' GL

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT-OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Subsequent of water encroachment

(NOTE: Report results of multiple completion or zone change on Form 9-330.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 7-13-80 3630' PBD. Pulled 2 3/8" tubing, Ran Gamma Ray and Neutron Logs. Set Retrievamatic Packer at 3496'. Well made water thru tubing.
- 7-15-80 3630' PBD. Reset packer at 3459'. Well making water thru tubing and between tubing and 4 1/2" csg. Reset packer at 3393'. Well making water thru tubing. Dry gas between tubing and 4 1/2" csg. Set cement retainer at 3409'.
- 7-16-80 3630' PBD. Set Retrievamatic at 3405', pressured up to 2000 PSI, held OK.
- 7-17-80 3630' PBD. Reran 108 jts. 2 3/8" 4.7# J-55 EUE tubing; 3356' landed at 3366'.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED DeLasso DeLasso TITLE District Manager DATE 7-28-80



(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: _____

*See Instructions on Reverse Side

NMOCC

BY 9/8