

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
Sun Oil Company

3. ADDRESS OF OPERATOR  
2525 N.W. Expressway, Okla. City, OK 73112

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit Letter P, 850' FSL & 1135' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
NM-047

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A

7. UNIT AGREEMENT NAME  
N/A

8. FARM OR LEASE NAME  
New Mexico Federal N

9. WELL NO.  
6-E

10. FIELD OR WILDCAT NAME  
Basin - Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 6-T30N-R12W

12. COUNTY OR PARISH | 13. STATE  
San Juan | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6042' GR

REQUEST FOR APPROVAL TO:      SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF      

FRACTURE TREAT      

SHOOT OR ACIDIZE      

REPAIR WELL      


PULL OR ALTER CASING      

MULTIPLE COMPLETE      

CHANGE ZONES      

ABANDON\*      

(other) Drilling \_\_\_\_\_



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-12-80 - Put well on orifice well tester. Loaded tbg with 2% KCL water. unseated pkr. & circ. hole. Started washing down. Unable to wash below 6,880'. Pooh. GIH with Ret. head to 6,880'. Unable to go deeper. Attempt to rotate - Heavy. Torque. Pulled up 10 stds.

7-13-80 - Finished Pooh. Ran impression block on wireline. No interpretation. GIH with rotary shoe. Tagged up @ 6,890'. Drld. sand bridge & fell through. Tagged up @ 6,910' - circ. pulled up 10 stds.

7-15-80 - GIH w/10 stds. - Tagged up @ 6,910'. Pooh. GIH w/Baker Ret. head & latch onto RBP @ 6,910'. Pulled up hole 90' & hung up. Attempted to free RBP. Pushed same back to 6,910'. Unable to move RBP. Jarred off of same. Pooh.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Deanna C. [Signature] TITLE Prod. Staff Assoc. I DATE 7-21-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

ACCEPTED FOR RECORD  
AUG 1 1980  
~~FEB 6 1980~~

\*See Instructions on Reverse Side

FARMINGTON DISTRICT  
BY [Signature]

NMCCO

N.M. 6-E cont'd.  
Page 2

- 7-16-80 - GIH w/3-3/4" x 3-1/16" x 10' mill. No progress. Turning on Btm. Tooh. Btm of mill unmarked.
- 7-17-80 - GIH w/3-3/4" x 1-7/8" overshot. Latched onto plug @ 6,910'. Jarred on same. Grapple slipped off. Pooh. GIH w/3-3/4" overshot. Latched onto plug @ 6,910'. Grapple slipped off. Pooh.
- 7-18-80 - GIH w/3-3/4" Flat Btm Mill. Tagged up @ 6,910'. Milled to 6,913'. Circ. hole clean.