

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐  
2. NAME OF OPERATOR  
Sun Oil Company  
3. ADDRESS OF OPERATOR  
2525 N.W. Expressway  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 850/S + 1135/E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Drill ☒

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED  
AUG 8 1980  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
NM 047  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A  
7. UNIT AGREEMENT NAME  
N/A  
8. FARM OR LEASE NAME  
New Mexico Federal -N-  
9. WELL NO.  
6E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 17-T30N-R12W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-25-80 - POOH w/Mill. GIH w/Rotary Shoe (3-3/4" x 3 - 1 1/16") & 4' Extension. Tagged plug @ 6,918'.  
7-26-80 - GIH w/Rotary Shoe. Tagged up @ 6,920'. Milled to 6,921' POOH. Rotary shoe wore smooth. GIH w/New Rotary Shoe tagged up @ 6,921'. Milled to 6,922'. Unable to reverse or circ. the long way. POOH.  
7-27-80 - Finished POOH. Rotary shoe wore smooth. GIH w/ overshot & grapple. Latched on to fish. POOH. Rec'd 2 large pieces of fish. Grapple forced open. GIH w/overshot & grapple. Latched onto fish. POOH.  
7-28-80 - RU go. Dumped 15' cmt on plug. Rd go.  
7-29-80 - GIH w/3-7/8" Mill w/ 8 - 3-1/8" D.C. Tagged TOC 6,950'. Drld 11' of hard cmt. to 6,916'. Milled to 6,917'. POOH - Mill worn smooth. One 5" piece of control bar inside mill. GIH w/Mill. Milled to 6,919'. Mill worn smooth. GIH w/Mill.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jeanne Owens TITLE Prod. Staff Assoc I DATE 8/1/80

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

AUG 12 1980

FARMINGTON DISTRICT

BY BW

\*See Instructions on Reverse Side

NM 000

- 7-30-80 - Finished GIH to 6,919'. Milled to 6,921'. Started pushing fish down through sand to 6,942'. Circ. POOH - LDDC. PU 4-1/2" Mod 'R' Pkr. GIH set pkr. @ 6,848'.
- 7-31-80 - Loaded Tbg. RU Schlumberger. GIH w/ 1-11/16" Tbg Gun - Set down @ 6,922'. Drug up hole to 6,918'. POOH w/Gun. Rel Mod "R" Pkr. POOH. PU Mill & GIH.
- 8-1-80 - Finished GIH. Tagged soft sand @ 6,914-214' D-A set down @ 6,934'. RD D-A. GIH w/Baker Mod "R" & set @ 6,905'. Swabbed tbg. down to 5,500'. RU Howco. Acidize down tbg. w/400 gal. 15% HCL. csg press. Equalized w/tbg. press. during last part of acid job. Rel Pkr. PU to 6,785'. Reset pkr.