

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1155'N, 1790'W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒ XX  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 0607

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Sunray

9. WELL NO.  
1A

10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 11, T-30-N, R-10-W  
NMPM

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6627' G

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

2-6-81: PBD 5960'. Tested caing to 3500#, OK. Perfed Lower Point Lookout:  
5729,5759,5775,5782,5804,5833,5840,5867,5882,5912,5930 W/1 SPZ. Fraced  
w/35,000# 20/40 sand, 70,100 gal. wtr. Flushed w/ 7600 gal. wtr.

Perfed Upper Point Lookout:  
5367,5376,5382,5387,5392,5424,5488,5537,5547,5552,5568,5574,5580,5600,  
5605,5621,5626,5642,5668,5673,5683' W/1 SPZ.  
Fraced w/ 60,300# 20/40 sand, 149,000 gal. wtr. Flushed w/7300 gal. wtr.

2-7-81: Perfed Cliff House & Menefee:  
4917,4924,4931,4960,4973,5026,5032,5046,5087,5095,5102,5116,5185,5199,5221,5230,  
5235,5272,5297,5304' W/1 SPZ. Fraced w/ 62,000# 20/40 sand, 124,000 gal. wtr.  
Flushed w/ 6900 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Al. P. Quisco TITLE Drilling Clerk DATE Feb. 17, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: