DEPARTMENT OF THE INTERIOR	5. LEASE SF-081098
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME-
1. oil gas	8. FARM OR LEASE NAME Florance 9. WELL NO.
2. NAME OF OPERATOR	122
Tenneco 0il Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME  Basin Dakota/Pictured Cliff
720 S. Colo. Blvd., Denver, CO 80222  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL:	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  Sec. 10: T30N: R9W  12. COUNTY OR PARISH 13: STATE  San Juan New Mexico
AT TOTAL DEPTH:	14. API NO. 74-8 2 1,233
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15) ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  PULL OR ALTER CASING	NOTE: Report results of multiple completion or zone
CHANGE ZONES  ABANDON*  (other) Report on Completion Operations	amulanten
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
3/6-3/24/80	교육 수 있는 사람들이 가는 것이 되었다. 기계 기계 기
MIRUCU on 3/6/80. Press. tested csg to 3500-Dakota w/2 SPF @ 7338-40, 7388-90, 7422-33, down perfs @ 3100 PSI w/2000 gal 15% HCL. Fr containing 80000# 20/40 sand and 25000# 10/2 Kicked w/N2. Set Model F packer @ 7288'. Per 2978-81, 2962-67. Spotted 300 gal 15% HCL ac Installed wellhead. Kicked PC around w/N2. F	7480-92, 7539-41, 7552-58. Broke ac'd Dakota w/80000 gal of 30# gel 0 sand. Landed 2 3/8" tbg 0 7300'. f'd Pictured 61iff w/2 SPE-0 2987-94, ross perfs. Landed 2 3/8" tbg 0 2960.
RDMOCU on 3/24/80.	Cutte and the following the control of the control
Subsurface Safety Valve: Manu. and Type	DON CAS
18. I hereby certify that the foregoing is true and correct	96T.30
(This space for Federal or State office use)	
APPROVED BY TITLE	DATE 15 TO PERSON
CONDITIONS OF APPROVAL, IF ANY:	enno de la constitución de la co

\*See Instructions on Reverse Side