

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
910'S, 845'E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other)	

5. LEASE
SF 080376

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 32-9 Unit

8. FARM OR LEASE NAME
San Juan 32-9 Unit

9. WELL NO.
14B

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 9, T-31-N, R-9-W
N.M.P.M.

12. COUNTY OR PARISH | 13. STATE
San Juan | New Mexico

14. API NO.


15. ELEVATIONS (SHOW DF, KDB, AND WD)
6598' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-26-80: TD 3879'. Ran 89 joints 7", 20#, K-55 intermediate casing 3868' set at 3879'. Cemented w/ 414 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of Cement 3350'.

3-29-80: TD 2430', Ran 79 joints 4 1/2", 10.5#, K-55 casing liner 2585' set at 2430'. Float collar set at 6151'. Cemented w/424 cu. ft. cement. WOC 18 hours.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. P. Busco TITLE Drilling Clerk DATE March 31, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____ **ACCEPTED FOR RECORD**

11-300

APR 3 1980

*See Instructions on Reverse Side

BY M. L. Kuchera