

F 30-045-24347 5-27-80

F. loc. 1600/S: 945/E Elev. 6471 GL Spd. 7-1-82 Comp. 12-12-82 8045- PB 7997
Casing S. 10 3/4 @ 300 W 250 Sx. Int. 7 5/8 @ 3020 W 350 Sx. Pr. 5 1/2 @ 800 W 500 Sx. T. 2 1/4 @ 7723
Csg Perf. 7814-7990 Prod. Slim. 500 F Good

note BOB

TRANS

I.P. _____		MCF/D After _____		Hrs. _____	Slip _____	psi After _____	Days GOR _____	Grav. _____	1 st Del. _____	_____		
TOPS		NITD	X	Well Log		TEST DATA						
Kirtland		C-103	☒	Plat	X	Schd.	PC	Q	PW	PD	D	Ref.No.
Fruitland	3060	C-104	☒	Electric Log	☒							
Pictured Cliffs	3304		☒	C-122	☒							
Cliff House	5211	Dlr		Dla								
Menefee		Dair		Doc								
Point Lookout	5604	NIT ready that want that we can if more production abandon that only 10-3-83 at amount to the well (a 9430) + 24 1/2' on ft. 12-15 805 casing ports										
Morcos												
Gallup	6770											
Sonostee												
Greenhorn	7697											
Dakota	7767											
Morrison												
Entrada												

E 320

E 320