UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		Budget Bure	au No. 42-R1424
	5. LEASE		
1	ł		

DEPARTMENT OF THE INTERIOR	NM 03358		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
CHARDY NOTICES AND DEPORTS ON MELLS	7. UNIT AGREEMENT NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	NEBU Agrmt. #1, Sec. 929		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas sm	Northeast Blanco Unit		
well gas X other	9. WELL NO.		
2. NAME OF OPERATOR	208		
Blackwood & Nichols Co., Ltd.	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	South Los Pinos-Fruitland PC		
P.O. Box 1237, Durango, Co. 81301	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
below.) AT SURFACE: 790' F/SL - 1750' F/WL	N-12-31N-7W		
AT SURFACE: 790' F/SL - 1750' F/WL AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE		
AT TOTAL DEPTH: Same	San Juan New Mexico		
oane	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6541' GL		
TEST WATER SHUT-OFF			
FRACTURE TREAT			
SHOOT OR ACIDIZE REPAIR WELL			
PULL OR ALTER CASING	(NOTE: Report results of multiple ampletion or zone change on Form 9-350) 1391		
MULTIPLE COMPLETE	011 000 1987		
CHANGE ZONES	OIL CON. COM.		
ABANDON* [] [] (other) Tight Formation Test X	DIST. 3		
(other) Tight Formation lest X			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	rectionally drilled, give subsurface locations and		
Ran Multi-Spaced Neutron, Gamma Ray-Neutron, Variable Spaced Density and Cement Bond Logs. Displaced water with nitrogen. Perforated Pictured Cliffs Zone with four holes per foot per interval; 3477', 3489', 3509', 3521', 3547', 3561' and 3570'. Ran 122 jts. 2 3/8" 4.7# J-55 EUE tubing; 3560' landed at 3566'. Will run shut-in and back pressure tests (natural).			
, , , , , ,			
Subsurface Safety Valve: Manu. and Type	Set @ Ft.		
18 Hiereby certify that the foregoing is true and correct			
SIGNEDA LO DELASSO LOOS TITLE DISTRICT Mana	ger 4-21-81		
(This space for Federal or State offi	ce use)		
APPROVED BY TITLE	DATE		
CONDITIONS OF APPROVAL, IF ANY:			
	. on atabal		
	Hoberthal FOR RECORD		

*See Instructions on Reverse Side

NMOCC

APR 29 1981

FARMINGTON DISTRICT