well

N.M.

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

other

5.	LEASE
	SF 078214
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
7.	UNIT AGREEMENT NAME
8.	FARM OR LEASE NAME
	McCord
9.	WELL NO. 5-E
10.	FIELD OR WILDCAT NAME
İ	Basin-Dakota
11.	SEC., T., R., M., OR BLK. AND SURVEY OF AREA
	Sec 27, T30N, R13W, NMPM
12.	COUNTY OR PARISH 13. STATE

UNION TEXAS PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR
P.O. Box 808, Farmington, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 950' FSL & 1725' FEL
AT TOP PROD. INTERVAL: same as above.
AT TOTAL DEPTH: same as above.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15, ELEVATIONS (SHOW DF, KDB, AND WD) 5740 G1

San Juan

14. API NO.

REQUEST FOR APPROVAL TO: SUBSETEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other) Complete re-seeding and

gas

2. NAME OF OPERATOR

 \mathbf{X}

SUBSEQUENT REPORT OF THE SUBSECUENT REPORT OF THE SUBSECUENT REPORT OF

(NOTE: Report results of multiple completion or zone change on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Location was re-seeded with BLM seed mix #2, and above ground equipment

was painted with Federal Standard Brown, #595a-30318.

RECEIVED

OIL CON. DIV.

Subsurface Safety Valve: Manu. and Typ	· · · · · · · · · · · · · · · · · · ·		Set @ Ft.
18. I hereby certify that the foregoing is	true and correct TITLEField Oper. Mangr.	DATE	9/28/82
1	(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE	

TRESPIED FOR NECORD

*See Instructions on Reverse Side

JAN 14 1983

