UNITED STATES

5. LEASE
SF-081239
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

DEPARTMENT OF THE INTERIOR	SF-081239	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME	
1 oil gos -	Holder "A"	
1. oil gas X other	9. WELL NO.	
2. NAME OF OPERATOR	#1-E	
Southland Royalty Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Rasin Dakota/ Flora Vista Gallup	
P.O. Drawer 570, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.) AT SURFACE: 1520' FNL & 1070' FEL	Section 6, T30N, R12W 12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL:	San Juan New Mexico	
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5986' GL	
TEST WATER SHUT-OFF	1001E: Report results of multiple domplitic for change on Form 9-1308	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	e all pertinent details, and give pertinent dates irectionally drilled, give subsurface is sations and	
6-19-81 Spudded 12-1/4" surface hole at 1:30 P	.M. 6-18-81 and drilled to	
total depth of 240'. Ran 5 joints (22	3.22') of 8-5/8", 24#, K-55	
casing set at 236'. Cemented with 140 sacks of Class "B" Neat		
with 1/4# gel flake per sack and 3% Ca	Cl ₂ . Plug down at 7:00 P.M.	
6-18-81. Cement circulated to surface	·••	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
18. I hereby certify that the foregoing is true and correct		
SIGNED R. E. Fielder TITLE District Engi	neer DATE June 22, 1981	
(This space for Federal or State office use)		

*See Instructions on Reverse Side

APPROVED BY _______CONDITIONS OF APPROVAL, IF ANY: