

# STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

### OIL CONSERVATION DIVISION

OIL COM. DIV. Page 1
DIST. 3 Revised 10/01/78

This form to net to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

l ocarion		ONOCO INC		Lease _		SE	Well No. 3M (MD)	
of Well:	Unit	C Sec. 20	Twp30	Rge	10		SAN JUAN	
Upper	NAME OF RESERVOIR OR POOL			TYPE OF (OH or (		METHOD OF PROD.	PROD. MEDIUM (The. or Cag.)	
MESA VERDE			GAS		FLOW	TBG.		
Completien	DAKOTA			GAS		FLOW	TBG.	
	Hour, date s	than in	PRE-FL	OW SHUT-IN	PRESSURE DATA	A	100.	
Completion	modellon 10-04-95		11-0	Length of time shut-in  11-DAYS  Length of time shut-in  11-DAYS		Steb	Stabilized? (Yes or No) Stabilized? (Yes or No) NO	
Completion			1			State		
				FLOW TEST	NO. 1			
10-15-95					Tono and a second		LOWER	
(hour, dete)		LAPSED TIME SINCE#	Upper Completion	SURE Lower Completion	PROD. ZONE TEMP.		REMARKS	
10-13	-95	!-DAY	350	605		ROTU ZONE	S SHUT-IN	
10-14	-95	2-DAYS	400	620			S SHUT-IN	
10-15	10-15-95 3-DAYS		425	695		BOTH ZONES SHUT-IN		
10-16	<u>-95</u> _	1-DAY	430	295			E FLOWING	
10-17	<u>-95</u>	2 -DAYS	433	109			E FLOWING	
						33.73.7		
toduc <del>ti</del> or	rate du	uring test						
ii:		BOPI	D based on	Rhie in		_	GOR	
25:			Mon	DUS. 10	Hour	s Grav.	GOR	
						r):		
Upper He	our, date sh	ut-in	MID-TE	ST SHUT-IN PI	RESSURE DATA			
ometetion	our, date sh				St press. palg Stabi		ized? (Yes or No)	
			Length of time shut					

#### FLOW TEST NO. 2

amenced at (hour, de	10)中本			Zone producing (Upper or Lowert:			
TIME (hour, dete)	LAPSED TIME SINCE 中丰		UNE	PROD. ZONE TEMP.	REMARKS		
		Upper Completion	Lewer Completion		REMA	ANKS	
				ļ			
· · · · · · · · · · · · · · · · · · ·	<del> </del>						
	1	ļ					
·	<del></del>	<del> </del>					
						-	
					[ ]		
iduction rate of	luring test						
:	ВОР	D based on	Bbls. in	Hours.	Grav	GOR	
s:	···	мсі	PD: Tested thru	(Orifice or Meter	):		
						-	
<del></del>						, <u> </u>	
ereby certify t	hat the informati	on herein contain	ed is true and co	mplete to the bes	et of my knowledge.		
proved	il Careerasion I	Rolunsen	19 (	Operator	CONOCO INC.	1100	
New Mexico O		1 3 1995	E	S <b>v</b> _	CONOCO INC.	LIPS	
		1 0 1000	_	DDOD	LICTIONS	<b>PECIALIST</b>	
<del></del>	DEPUTY OIL 8	GAS INSPECTOR		ide LUUU	UCTION 3	I LUIALIO I	
le		2.5	г	)ste	CONOCO	INC	

### NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within in days after actual completion of the well, and annually thereafter as prescribed by the er authorizing the multiple completion. Such tests shall also be commenced on all stiple completions within seven days following recompletion and/or chemical or fractical test and whenever remedial work has been done on a well during which the ser or the tubing have been distrutbed. Tests shall also be taken at any time that comnication is suspected or when requested by the Division.

At least 72 hours prior to the commencement of any packer leakage test, the operator it notify the Division in writing of the exact time the test is to be commenced. Offset rators shall also be so notified.

The packer leakage test shall commence when both zones of the dual completion are tem for pressure stabilization. Both zones shall remain shut-in until the well-head sture in each has stabilized, provided however, that they need not remain shut-in more is seven days.

For Flow Test No. 1, one zone of the dual completion shall be produced at the normal of production while the other zone remains shut-in. Such test shall be continued for an days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack a pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be shut-in, in accorice with Paragraph 3 above.

Flow Test No. 2 shall be conducted even though no leak was indicated during Flow  $\pi$  No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway pount) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least rwice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).