

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Joel B. Burr, Jr.
3. ADDRESS OF OPERATOR
300 W. Arrington, Suite 300, Farmington, NM
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1185' FSL & 690' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM 024158
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Foothills A
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Fulcher Kutz Pictured Cliff
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 20, 30N, 12W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5679' G.L.

RECEIVED
(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DIV.
3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 5 1/4" hole to 2000'. Ran IES, CNL-FDC open hole logs. Ran 2 7/8" 6.4#/ft 10 rd N EUE casing. Landed casing at 1996' with float collar at 1963'. Cemented with 336 cubic feet 65-35 poz with 12% gel and 12 1/2# Gilsonite per sack followed by 130 cubic feet 50-50 poz + 2% gel + 12 1/2# Gilsonite per sack. Circulated 84 cubic feet to surface. Job complete 1545 hours 5/27/83.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John Alexander TITLE Agent DATE 6/1/83
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

NMOC

FARMINGTON DISTRICT

67

5m

